



- 30W, 50W, 80W and 110W models replacing up to 400W HID
- Light panel can rotate once the base is tightened to direct light out of the fixture
- Includes a fan and thermal sensor to run cool and ensure a long and bright life
- Enclosed fixture safe and approved for damp locations
- LED-8090-HV: 277-480V (can be used on 347V)
- "D" Models dim to 50% by selecting "LO" on the switch located on the top of the lamp only
- Field-adjustable light output via physical switch on the product

FLEXCOLOR
SWITCH BETWEEN 4 CCTs



PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT*	BASE	DLC CODES
LED-8087E345D-G4	844006074432	100W HID	30W	3500/4200/4300	FLEXCOLOR 3000K/4000K/ 5000K	E26	N/A
LED-8087M345D-G4	844006074456	100W HID	30W	3500/4200/4300		EX39	P1CK54P3
LED-8088E345D-G4	844006074470	175W HID	50W	6400/6900/7200		E26	N/A
LED-8088M345D-G4	844006074494	175W HID	50W	6400/6900/7200		EX39	P6YHOJXP
LED-8089M345D-G4	844006074517	250W HID	80W	10600/10700/10800		EX39	PE1R64EU
LED-8090M345D-G4	844006074524	400W HID	110W	14500/15400/15700		EX39	PTGQIRSF
LED-8090M345D-G4-HV	844006074760	400W HID	110W	14500/15400/15700		EX39	PLQZ2S2U

* FLEXCOLOR VALUES — MIN/DEFAULT/MAX





🇨🇦 347 VOLT OPTIONS FOR CANADA 🇨🇦

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT*	BASE	DLC CODES
LED-8087E345CD-G4	844006074425	100W HID	30W	3500/4200/4300	3000K/ 4000K /5000K	E26	N/A
LED-8087M345CD-G4	844006074449	100W HID	30W	3500/4200/4300	3000K/ 4000K /5000K	EX39	PNARUA94
LED-8088E345CD-G4	844006074463	175W HID	50W	6400/6900/7200	3000K/ 4000K /5000K	E26	N/A
LED-8088M345CD-G4	844006074487	175W HID	50W	6400/6900/7200	3000K/ 4000K /5000K	EX39	PLK1XZP2
LED-8089M345CD-G4	844006074500	250W HID	80W	10600/10700/10800	3000K/ 4000K /5000K	EX39	PF34RTPP

* FLEXCOLOR VALUES — MIN/DEFAULT/MAX

LUMENS

LED-8087

	WATTAGE	CCT	LUMENS
MIN	15W	MIN 3000K	1750
	15W	DEFAULT 4000K	2100
	15W	MAX 5000K	2150
DEFAULT/MAX	30W	MIN 3000K	3500
	30W	DEFAULT 4000K	4200
	30W	MAX 5000K	4300

LED-8088

	WATTAGE	CCT	LUMENS
MIN	25W	MIN 3000K	3200
	25W	DEFAULT 4000K	3450
	25W	MAX 5000K	3600
DEFAULT/MAX	50W	MIN 3000K	6400
	50W	DEFAULT 4000K	6900
	50W	MAX 5000K	7200

LED-8089

	WATTAGE	CCT	LUMENS
MIN	40W	MIN 3000K	5300
	40W	DEFAULT 4000K	5350
	40W	MAX 5000K	5400
DEFAULT/MAX	80W	MIN 3000K	10600
	80W	DEFAULT 4000K	10700
	80W	MAX 5000K	10800

LED-8090

	WATTAGE	CCT	LUMENS
MIN	55W	MIN 3000K	7250
	55W	DEFAULT 4000K	7700
	55W	MAX 5000K	7850
DEFAULT/MAX	110W	MIN 3000K	14500
	110W	DEFAULT 4000K	15400
	110W	MAX 5000K	15700

