



Color: Bronze

Weight: 41.4 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	385W
120V	N/A	Color	4000K (Neutral)
208V	N/A	Temp	
240V	N/A	Color Accuracy	83 CRI
277V	N/A	L70	
Input Watts	293.2/317.7/361.6W	Lifespan	100,000 Hours
		Lumens	45659/49080/55139 lm
		Efficacy	155.7/154.5/152.5 lm/W

## Technical Specifications

### Field Adjustability

#### Field Adjustable (Wattage):

Field adjustable light output in 3 discrete steps:  
Extra Large Housing: 385W/345W/300W/345W  
(factory default 385W)

### Compliance

#### UL Listed:

Suitable for wet locations

#### IP Rating:

Ingress protection rating of IP66 for dust and water

#### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

#### DLC Listed:

This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at [designlights.org](https://designlights.org) to confirm the qualification status of a specific SKU prior to specification or purchase.

### LED Characteristics

#### LEDs:

Long-life, high-efficacy, discrete, surface-mount LEDs

#### Color Consistency:

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

#### Color Stability:

LED color temperature is warranted to Shift no more than 200K in color temperature over a 5-year period

#### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for (SSL) Products, ANSI C78.377-2017.

### Electrical

#### Driver:

300W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.67A

345W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.72A

385W: Constant Current, Non-Class 2, 480V, 50/60 Hz, 480V: 0.81A

#### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

#### THD:

5.82% 480V

#### Power Factor:

93.4% at 480V

#### Surge Protection:

Line to Line: 10 kV  
Line to Ground: 6 kV

### Performance

#### Lifespan:

100,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations

#### Wattage Equivalency:

Equivalent to 1,500W Metal Halide

### Optical

#### IES Classification:

The Type V distribution produces light in a wide and uniform 360° pattern that is perfect for large outdoor areas such as parking lots, corporate parks and retail settings

#### Bug Rating:

385W: B5 U0 G4  
345W: B5 U0 G3  
300W: B5 U0 G3



## Technical Specifications (continued)

### Construction

#### Cold Weather Starting:

The minimum starting temperature is -40°F (-40°C)

#### Ambient Temperature :

Max Power Temp Rating: 104°F (40°C)

Middle Power Temp Rating: 43°C (110°F)

Low Power Temp Rating: 47°C (116°F)

#### Housing:

Die-cast aluminum

#### Tilt Increment:

Rotates in 5 degree increments

#### Lens:

Polycarbonate lens

#### Reflector:

Aluminum reflector with white polycarbonate

#### Vibration Rating:

3G vibration rating per ANSI C136.31

#### Effective Projected Area (EPA):

1 Fixture: 0.7

2 Fixtures at 90°: 1.11

2 Fixtures at 180°: 1.41

3 Fixtures at 90°: 1.81

4 Fixtures at 90°: 1.81

#### Gaskets:

High-temperature silicone gaskets

#### Finish:

Formulated for high durability and long-lasting color

#### Green Technology:

Mercury and UV free. RoHS-compliant components.

### Installation

#### Mounting:

2 3/8" slipfitter mount with stainless steel hardware

### Sensor Settings

#### Multi Level Motion Sensor:

/WS4 sensor options use state-of-the-art surface mount technology (SMT), just like cellular phones and beepers. SMT gives you more reliability, greater RF immunity. This compact sensor that can fit neatly where others cannot. This sensor technology automatically affects the state of operation for lighting systems or individual luminaires based upon detecting the presence or absence of movement for both people as they exit/enter, or for the motion of moving vehicles within the sensors viewing area. The wide 180° viewing angle can detect movement along the entire side of a building with only one compact sensor. The hard lens is molded as part of the case, vandalproof, rainproof, bugproof and absolutely sealed. Sensor functions best when movement is across its detection pattern, not towards the sensor.

#### Handheld Wireless Configuration Tool:

Adjust settings using handheld wireless configuration tool (catalog# WSREM). Only available with 0-10V dimming driver options. [Handheld wireless configuration tool available here.](#)

### Other

#### 10-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of ten (10) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Dimensions



## Features

- 0-10V dimmable standard
- IP66 Rated
- 100,000-Hour LED lifespan
- 10-Year, No-Compromise Warranty

## Ordering Matrix

Family	Housing Size	Distribution	Mounting	Color Temp	Finish	Driver	Options
ALED	XL	5T	SF	N		/480	/WS4
	<b>M</b> = Medium (150W/90W/78W) <b>L</b> = Large (260W/220W/170W) <b>XL</b> = Extra Large (385W/345W/300W) <b>S</b> = Small (80W/60W/40W)	<b>2T</b> = Type II <b>3T</b> = Type III <b>4T</b> = Type IV <b>5T</b> = Type V <b>AT</b> = Auto Dealership Optic	<b>Blank</b> = Universal Pole Mount <b>SF</b> = Slipfitter <b>WM</b> = Wall Mount	<b>Blank</b> = 5000K Cool <b>Y</b> = 3000K Warm <sup>1</sup> <b>N</b> = 4000K Neutral	<b>Blank</b> = Bronze <b>W</b> = White <b>B</b> = Black	<b>Blank</b> = 120-277V, 0-10V Dimming <b>/480</b> = 480V, 0-10V Dimming	<b>Blank</b> = No Option <b>/7PR</b> = 7 Pin Twistlock Receptacle <b>/WS2</b> = Wattstopper, 20ft lens <b>/WS4</b> = Wattstopper, 40ft lens <sup>3</sup>

<sup>1</sup> Dark sky approved in 3000K, available only on Small and Medium fixtures

<sup>2</sup> 480V available only on Medium, Large & Extra Large fixtures

<sup>3</sup> Wattstopper option available only on Large & Extra Large fixtures