

Project:

Type:

Prepared By:

Date:



UPC: 192552037648

### Features and Benefits

Selectable color temperature: 2700/3000/3500/4000/5000K

Energy-efficient replacement for incandescent and halogen lamps

Produces rich and vibrant colors >90CRI

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

Dimmable; see Dimmer Compatibility List

## Technical Specifications

### Performance

#### Product Type:

Reflector, CCT-Adjustable

#### Description:

CCT-selectable lamps replace up to 150W conventional incandescent.

#### Wattage Equivalency:

65W Incandescent

#### Input Wattage:

7W

#### Lumens:

666lm @ 2700K; 694lm @ 3000K; 732lm @ 3500K;  
724lm @ 4000K; 677lm @ 5000K

#### Efficacy:

98lm/W @ 2700K; 100lm/W @ 3000K; 104lm/W @  
3500K; 104lm/W @ 4000K; 99lm/W @ 5000K

#### L70 Lifespan:

25,000-Hour LED lifespan based on IES LM-70 results

### Electrical

#### Driver:

Constant Current 120V 60 Hz @ 120V: 80 mA

#### Power Factor:

>0.7

#### Dimmable:

Yes, dimmable down to 10% on compatible TRIAC/ELV dimming systems. See Dimmer Compatibility List.

#### Input Voltage:

120V

#### Operating Temperature:

-4°F to 113°F (-20 to 45°C)

#### Flicker:

<30%

### LED Characteristics

#### Beam Angle:

100°

### Color Temperature:

Field adjustable via dip switch  
2700/3000/3500/4000/5000K

Default: 3000K

### Color Accuracy (CRI):

≥90

### R9 Value:

High color performance with R9 no greater than 0

### Color Consistency:

<4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

### Installation

#### Base Type:

E26 Edison

### Construction

#### Shape:

BR30

#### Finish:

White

## Technical Specifications (continued)

**Endcap Material:**

Aluminum

**Enclosure Material:**

Plastic

**Lens Finish:**

Frosted

**Compliance**

---

**Listings:**

UL Listed

**Environment:**

Suitable for use indoors in dry and damp environments.

**Fixture Rating:**

Suitable for use in enclosed fixtures

**Energy Star Approved:**

No

**Certification Model Number:**

P10035(BR30-7-9CCT-DIM)

**California Title 20 Compliant:**

Can be used to conform with the requirements of California Title 20

**California Title 24 JA8 Compliant:**

No

**California Energy Commission (CEC) Status:**

Lawful for Sales in California

**IESNA LM-79 & LM-80 Testing:**

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

**RoHS:**

Mercury and UV free. RoHS-compliant components.

**FCC:**

Complies with Part 15 of the FCC Rules

**Other**

---

**3-Year, No-Compromise Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	16.93	12.6	12.8
PALLET	768	46.46	37.8	51.2

## Dimension

