

Project:

Type:

Prepared By:

Date:



UPC: 019813834832

Features and Benefits

- Natural light detection
- On-off functionality
- Hold time: 1 minute, 5 hours, or 8 hours
- Standard 3.5mm AUX port connection
- Threshold levels at 20 lx /50 lx /100 lx /300 lx
- Suitable for use in enclosed luminaire
- Do not expose directly to water
- Use only one module per lamp

Technical Specifications

Performance

Product Type:
DAYLIGHT Sensor

L70 Lifespan:
50,000 Hours

Electrical

Input Voltage:
15VDC

Max Input Current:
0.1A

Max Output Current:
0.02A

Lux Options:
20/50/100/300lux

Hold Time Options:
1min/5hr/8hr

Input Frequency:
5.8 GHz +/- 75MHz

Output Voltage:
10VDC

Operating Frequency:
5.8GHz

Operating Current:
20mA

Transmit Power:
1mW

Compliance

California Energy Commission (CEC) Status:

Lawful for Sales in California

Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	100	9.8	9.8	8
PALLET	10000	49.2	40	45.5

Dimension

