

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



UPC: 192552005562

Features and Benefits

- Replacement for high-output incandescent/halogen or ceramic metal halide
- Adjustable CCT to choose from 3000/4000/5000K
- Rated for use in enclosed fixtures in dry, damp, or wet locations
- 90+CRI provides high quality color rendering
- Shatterproof enclosure for rugged applications

Technical Specifications

Performance

Product Type:
PAR

Input Wattage:
19W

Lumens:
1,800lm

Efficacy:
163.6lm/W

L70 Lifespan:
15,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:
150W Halogen

Compliance

Enclosed Fixtures:
Suitable for use in enclosed fixtures

LED Characteristics

Color Temperature:
3000/4000/5000K CCT Adjustable

Color Accuracy (CRI):
90 CRI

Beam Angle:
40°

Electrical

THD:
<20%

Power Factor:
0.9

Dimmable:
Yes, dimmable down to 10% on compatible TRIAC/ELV dimming systems.

Operating Temperature:
-20°C to 45°C (-4°F to 113°F)

Input Voltage:
120V

Operating Frequency:
60 Hz

Construction

Shape:
PAR38

Endcap Material:
Aluminum

Enclosure Material:
Plastic

Installation

Base Type:
E26 Edison

Other

3-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	24	20.3	15.4	20
PALLET	432	47.24	41.34	37.01

Dimension

