

Project: \_\_\_\_\_ Type: \_\_\_\_\_ Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_



**Features and Benefits**

- Motion detection
- On-off functionality
- Slotted detection pattern
- Standby level options: off, 20% dim, 40% dim, or 60% dim
- Hold time options for motion detection: 30 seconds, 90 seconds, 5 minutes, 10 minutes
- Standard 3.5mm AUX port connection
- Do not use with enclosed metal luminaire
- IP20, don't expose directly to water
- Daylight Photocell built in with default threshold of 300 lx

<b>Technical Specifications</b>		
<p><b>Performance</b></p> <hr/> <p><b>Product Type:</b> PIR Sensor</p> <p><b>Electrical</b></p> <hr/> <p><b>Operating Temperature:</b> -20°C to 60°C</p> <p><b>Input Voltage:</b> 15VDC</p> <p><b>Max Input Current:</b> 0.1A</p> <p><b>Max Output Current:</b> 0.02A</p> <p><b>Detection Angle:</b> 120 degrees</p> <p><b>Max Mounting Height:</b> 19.7 ft</p> <p><b>Detection Radius:</b> 13.12 ft</p>	<p><b>Standby Dim Levels:</b> 0/20%/40%/60%</p> <p><b>Input Frequency:</b> 5.8 GHz +/- 75MHz</p> <p><b>Input Current @ 120V:</b> Max 0.1mA @15V</p> <p><b>Output Voltage:</b> 10VDC</p> <p><b>Operating Frequency:</b> 5.8GHz</p> <p><b>Operating Current:</b> 20mA</p> <p><b>Transmit Power:</b> 1mW</p> <p><b>Construction</b></p> <hr/> <p><b>For Use Outdoors in Open Fixtures:</b> No</p>	<p><b>Compliance</b></p> <hr/> <p><b>UL Listed:</b> Yes</p> <p><b>California Energy Commission (CEC) Status:</b> Lawful for Sales in California</p> <p><b>Other</b></p> <hr/> <p><b>5-Year, No-Compromise Warranty:</b> RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a>.</p>

**Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	100	9.8	9.8	8
PALLET	6400	45.1	39.4	39.4

**Dimension**

