

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Omni directional light distribution
- Suitable for horizontal or vertical installations
- Replaces 26W/32W G24d & G24q
- Plug and Play on existing Magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast
- Compatible with G24d / GX24d & G24q / GX24q installations
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Listed, UL Classified
- Rated for use in enclosed and open fixtures in dry or damp locations
- Non-Dimmable
- 5 Year No Compromise Warranty

Technical Specifications		
Performance	Beam Angle:	Enclosure Material:
Product Type: Compact	360°	Constructed from frosted, shatter-resistant polycarbonate
Input Wattage: 9W	Electrical	Housing Finish: White
Lumens: 1,200lm	THD: 20%	Lens Finish: Frosted
Efficacy: 133lm/W	Power Factor: >0.9	Installation
L70 Lifespan: 50,000-Hour LED lifespan based on IESlm-80 results and TM-21 calculations	Dimmable: Non-Dim	Base Type: 2-Pin G24d
Wattage Equivalency: 26W/32W G24d & G24q	Input Voltage: 120-277 Type B (Type A dependent on ballast)	Installation Method: UL Type A with Magnetic Ballasts & UL Type B (Dual Mode)
LED Characteristics	Operating Frequency: 50/60Hz	Burning Position: Universal
Color Accuracy (CRI): 80	Operating Temperature: -20°C to 45°C (-4°F to 113°F)	Other
Color Temperature: 3000K	Construction	Technology EQ: CFL
	Shape: PLC-O	

Technical Specifications (continued)

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

Listings:

UL Listed, UL Classified

Environment:

Damp / Enclosed

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Certification Model Number:

T10195(PLC-9-O-830-HYB)


Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
7	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	674	0	0	0

Dimension



Light Distribution

