



Color: Bronze

Weight: 6.9 lbs

<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	110/95/80W
120V	N/A	Color Temp	3500/4000/5000K
208V	N/A	Color Accuracy	80-82 CRI
240V	N/A	L70 Lifespan	100,000 Hours
277V	N/A	Lumens	10,563-14,631 lm
Input Watts	78.8-110.3W	Efficacy	124.2-140.4 lm/W

### Technical Specifications

#### Field Adjustability

##### Field Adjustable:

Field Adjustable Light Output:  
110W/95W/80W (factory default 80W)  
Color Temperature Selectable:  
3500K, 4000K and 5000K (factory default 4000K)  
On/Off Photocell (factory default "Off")

#### Compliance

##### UL Listed:

Suitable for wet locations

##### IP Rating:

Ingress protection rating of IP65 for dust and water

##### IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

##### DLC Listed:

This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at [designlights.org](http://designlights.org) to confirm the qualification status of a specific SKU prior to specification or purchase.

#### Performance

##### Lifespan:

100,000-Hour LED lifespan based on IESlm-80 results and TM-21 calculations

##### Driver:

110W: Constant Current, Class 1, 50/60 Hz, 480V, 480V: 0.24A  
95W: Constant Current, Class 1, 50/60 Hz, 480V, 480V: 0.20A  
80W: Constant Current, Class 1, 50/60 Hz, 480V, 480V: 0.17A

#### LED Characteristics

##### LEDs:

Long-life, high-efficacy, surface-mount LEDs

##### Color Consistency:

7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

##### Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

#### Electrical

##### Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 10%.

##### THD:

110W: 12.02% at 480V  
95W: 13.83% at 480V  
80W: 16.09% at 480V

##### Power Factor:

110W: 94.3% at 480V  
95W: 92.7% at 480V  
80W: 90.5% at 480V

##### Surge Protection:

Ring Wave LN4 kV/LN-GND 6 kV

##### Aux Power Supply:

Yes

##### Dim to Off:

Yes

##### Photocell:

Integrated photocell included with on/off switch (factory default: off)

**Technical Specifications (continued)**

**Construction**

**Cold Weather Starting:**

The minimum starting temperature is -40°F (-40°C)

**Maximum Ambient Temperature:**

Suitable for use in up to 104°F (40°C)

**Gaskets:**

High-temperature silicone

**Housing:**

Die-cast aluminum

**Lens:**

Polycarbonate lens

**Reflector:**

Polycarbonate

**Green Technology:**

Mercury and UV free. RoHS-compliant components.

**Finish:**

Formulated for high durability and long-lasting color

**Installation**

**Mounting:**

Surface and pendant mounting

**Optical**

**BUG Rating:**

110W: B4 U5 G5

95W: B4 U5 G5

80W: B3 U4 G5

**Other**

**5-Year Limited Warranty:**

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Ordering Matrix**

Family	Wattage	Color Temp	Shape	Finish	Driver	Controls	Battery Backup
PRT	110		S		/480		
	55 = 55/42/30W 80 = 80/70/60W 110 = 110/95/80W	Blank = 3500/4000/5000K Adjustable CCT	R = Round S = Square	Blank = Bronze W = White	Blank = 120-277V, 0-10V Dimming, On/Off Photocell /480 = 480V, 0-10V Dimming, On/Off Photocell	Blank = On/Off Photocell <sup>1</sup> /LC = Lightcloud /LCB = Lightcloud Blue <sup>2</sup>	Blank = None /E = Battery Backup <sup>3</sup>

<sup>1</sup> Integrated photocell can't be used when ordered with LC or LCB options

<sup>2</sup> Should not be combined with integrated fixture sensors

<sup>3</sup> Battery backup only available on 120-277V models