



Color: White

Weight: 1.4 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Performance

Product Type:

Surface Mount Battery Backup

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

Electrical

THD:

<20%

Power Factor:

0.9

Input Voltage:

100-277V

Operating Frequency:

60 Hz

Input Current @ 120V (mA):

60mA

Input Current @ 208V (mA):

100mA

Emergency Operation:

90 minutes

Battery Type:

Lithium Ion

Discharge Temperature:

32°F to 122°F (0°C to 50°C)

Storage Temperature:

-4°F to 77°F (-20°C to 25°C)

Storage Shelf Life:

1-year

Lightcloud

Operating Temperature:

41°F to 104°F (5°C to 40°C)

Installation

Mounting:

Surface Mount

Construction

Size:

9"

Shape:

Round

Finish:

White

Enclosure Material:

Metal

Trim Style:

Smooth

UV Protection:

No

Compliance

Listings:

UL Recognized

Environment:

Suitable for use indoors in dry and damp environments.

IC Rated:

No

Certification Model Number:

SM-9R-W/EMBB

California Title 20 Compliant:

Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:

No

Technical Specifications (continued)

California Energy Commission (CEC) Status:

Lawful for Sales in California

Other

Compatible Products:

Compatible with select Surface Mount Downlights, see complete Downlight Accessory Compatibility Guide.

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions

