

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Motion detection
- 360° detection through walls and objects
- Continuous detection pattern
- On-off functionality
- Standby level options: off, 20% dim, 40% dim, or 60% dim
- Hold time options for motion detection: 30 seconds, 90 seconds, 5 minutes, or 10 minutes
- If no motion is detected: lamp will be switched to 0-60% brightness
- If any motion is detected: lamp returns to 100% output to pre-defined hold time

Technical Specifications		
Performance	Standby Dim Levels:	Other
Product Type: PIR Sensor	0/20%/40%/60%	5-Year, No-Compromise Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .
L70 Lifespan: 50,000 Hours	Input Frequency: 5.8 GHz +/- 75MHz	
Electrical	Output Voltage: 10VDC	
Input Voltage: 15VDC	Operating Frequency: 5.8GHz	
Max Input Current: 0.1A	Operating Current: 20mA	
Max Output Current: 0.02A	Transmit Power: 1mW	
Detection Angle: 120 degrees	Compliance	
Max Mounting Height: 19.7 ft	California Energy Commission (CEC) Status: Lawful for Sales in California	
Detection Radius: 13.12 ft		

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	100	9.8	9.8	9
PALLET	10000	49.2	40	47.3

Dimension

