

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replacement for conventional fluorescent T8 and T12 linear tubes
- Dedicated External driver must be paired together with RAB tubes
- Can be installed using single ended or double ended wiring method
- Works with non-shunted sockets AND shunted sockets.
- 50,000 hour Lifespan
- Rated for use in enclosed and open fixtures in dry or damp locations
- Diffused frosted lens will maintain the same light quality over time
- Instant on full brightness
- Low Flicker less than 1%
- UL Classified, DLC Listed

Technical Specifications		
Performance	Color Accuracy (CRI):	Operating Temperature:
Product Type: Linear	≥80 CRI	-20°C to 45°C (-4°F to 113°F)
Input Wattage: 11W	Beam Angle: 220°	Input Voltage: Driver Dependent
Lumens: 2,050lm	Construction	Operating Frequency: 50/60Hz
Efficacy: 158lm/W	Shape: T8	Dimming: Yes with 0-10V dimmer. See Dimmer Compatibility List.
L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results	Endcap Material: Plastic	Other
Compliance	Enclosure Material: Glass	5-Year, No-Compromise Warranty: RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .
UL Listed: Suitable for damp locations	Installation	
Enclosed Fixtures: Suitable for use in enclosed fixtures	Base Type: G13	
LED Characteristics	Electrical	
Color Temperature: 3000K	THD: <25%	
	Power Factor: 0.9	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	50.8	6.3	7
PALLET	0	0	0	0

Dimension

