



<b>Project:</b>	<b>Type:</b>
<b>Prepared By:</b>	<b>Date:</b>

Driver Info		LED Info	
Type	Constant Current	Watts	12W
120V	0.11A	Color Temp	3000/3500/4000/5000/6500K
208V	0.06A	Color Accuracy	80 CRI
240V	0.06A	L70 Lifespan	50,000 Hours
277V	0.05A	Lumens	1,650 lm
Input Watts	12W	Efficacy	138

### Technical Specifications

#### Performance

**Wattage Equivalency:**

32W Fluorescent

**Input Wattage:**

12W

**Lumens:**

1,650lm

**Efficacy:**

138lm/W

**L70 Lifespan:**

50,000-Hour LED lifespan based on IES LM-70 results

#### Electrical

**THD:**

<25%

**Power Factor:**

>0.9

**Dimmable:**

Type B: TRIAC Dimming @ 120V only

Type A: 0-10V dimming with compatible dimmable fluorescent ballast and 0-10V Dimmer

**Input Voltage:**

Type A: Ballast dependent

Type B: 120-277V

**Operating Frequency:**

60 Hz

**Input Current @ 120V (mA):**

105mA

**Input Current @ 208V (mA):**

61mA

**Input Current @ 240V (mA):**

55mA

**Input Current @ 277V (mA):**

48mA

**Operating Temperature:**

-4°F to 104°F (-20°C to 40°C)

**Flicker:**

<40%

#### LED Characteristics

**Beam Angle:**

220°

**Color Temperature:**

Field adjustable via dip switch

3000/3500/4000/5000/6500K

**Color Accuracy (CRI):**

>80 CRI

**R9 Value:**

High color performance with R9 greater than 0

**Color Consistency:**

<6-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

**Color Stability:**

LED color temperature is warranted to Shift no more than 200K in color temperature over a 5-year period

**Color Uniformity:**

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

#### Installation

**Installation Method:**

UL Type A+B, Hybrid

**Base Type:**

G13

## Technical Specifications (continued)

### Construction

---

**Length:**  
4 ft

**Shape:**  
T8

**Finish:**  
White

**Endcap Material:**  
Plastic

**Enclosure Material:**  
Glass

**Lens Finish:**  
Frosted

### Compliance

---

**Listings:**  
UL Listed, UL Classified

**Environment:**  
Suitable for use indoors in dry and damp environments.

**Fixture Rating:**  
Suitable for use in enclosed fixtures

**DLC Listed:**  
This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at [designlights.org](https://designlights.org) to confirm the qualification status of a specific SKU prior to specification or purchase.

**Certification Model Number:**  
T10370(T8-12-48G-8CCT-HYB)

**California Title 20 Compliant:**  
No

**California Title 24 JA8 Compliant:**  
No

**California Energy Commission (CEC) Status:**  
Lawful for Sales in California

**NSF Listed:**  
Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

**RoHS:**  
Mercury and UV free. RoHS-compliant components.

**FCC:**  
Complies with Part 15 of the FCC Rules

### Other


---

**5-Year, No-Compromise Warranty:**  
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](https://rablighting.com/warranty).

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	50.63	6.18	7.05
PALLET	1000	51.42	37.87	49.33

## Dimension



## Features

Direct replacement for fluorescent lamps: F32T8/32W, F32T8/30W, F32T8/28W, F32T8/25W

TYPE A - plug-and-play compatible with most common commercial T8 electronic ballasts

TYPE B - can be wired directly to line voltage 120-277V. Can be wired using single- or double-ended method

Works with both shunted and non-shunted sockets

5 color temperatures in 1 SKU (3000K, 3500K, 4000K, 5000K, 6500K)

50,000-Hour lifespan

## Ordering Matrix

Family	Wattage	Length	Material	CRI/Color Temp	Driver	Wiring Method	Installation Method	Lens Finish
T8	12	48	G	8CCT			HYB	
	7.5 = 7.5W 10.5 = 10.5W 11 = 11W 12 = 12W 15 = 15W	24 = 2 ft 36 = 3 ft 48 = 4 ft	G = Glass GC = Glass Coated	8CCT = 80 CRI, 3000/3500/4000/5000/6500K CCT Adjustable	Blank = 120-277V	Blank = Single + Double Ended	HYB = Hybrid	Blank = Frosted C = Clear