

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replacement for conventional fluorescent T8 and T12 linear tubes
- Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Approximately 50% more energy efficient when compared to Fluorescent T8 lamps
- Works with non-shunted sockets ONLY.
- Separate wiring harness and socket kit accessory available
- 50,000 hour Lifespan
- Rated for use in enclosed and open fixtures in dry or damp locations
- Diffused frosted lens will maintain the same light quality over time
- Instant on full brightness
- Environmentally friendly, no mercury used
- NSF Listed: NSF/ANSI Standard 2 - Food Equipment - Splash Zone (Not for Direct Food Zone without additional fixture considerations)
- Phase cut dimming

Technical Specifications		
Performance <hr/> Product Type: Linear Input Wattage: 14.5W Lumens: 1,825lm Efficacy: 126lm/W L70 Lifespan: 50,000 Hours Wattage Equivalency: 32W Fluorescent Construction <hr/> Material: Coated Glass Shape: T8	Nominal Length: 4 ft Finish: Frosted For Use Outdoors in Open Fixtures: No LED Characteristics <hr/> Color Temperature: 4000K Cool White Color Accuracy (CRI): 80 CRI Beam Angle: 180° Installation <hr/> Base Type: G13 Installation Type: Type B, Single Ended wiring	Electrical <hr/> THD: <25% Power Factor: >0.9 Operating Temperature: -20°C to 45°C (-4°F to 113°F) Dimming: Yes with Phase dimmer. See Dimmer Compatibility List. Input Voltage: 120V Operating Frequency: 60 Hz Input Current @ 120V: 130mA

Technical Specifications (continued)

Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Compliance

UL Recognized:

Yes

UL Classified:

Yes

Certification Model Number:

T10088

NSF Listed:

Meets NSF/ANSI standards for use in Food Zone (non-contact), Splash, and Non-Food Zones. Tube guard required in open fixtures.

California Energy Commission (CEC) Status:

Lawful for Sales in California

Application:

Suitable for damp locations and totally enclosed fixtures.

DLC Listed:

This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at designlights.org to confirm the qualification status of a specific SKU prior to specification or purchase.


Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
49	4


Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	25	50.2	7.3	7
PALLET	1200	58.3	43.7	50.2

Wiring Diagram



Dimension



Light Distribution

