

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Compatible with RAB Type C T8 LED Lamps only
- Meets FCC Part 15 (Class B) Consumer Limits
- Short Circuit Overload and Open Load Protection
- Suitable for Dry and Damp Locations
- UL8750 Recognized Component
- Dimmable with 0-10V Dimmer
- Maximum Case Temperature: 75°C/167°F
- Input Frequency: 50/60 Hz
- THD: < 20%
- Type P
- Output Class 2

Technical Specifications		
<p>Performance</p> <p>Product Type: Linear</p> <p>Input Wattage: 15W</p> <p>Lumens: 2,100lm</p> <p>Efficacy: 127lm/W</p> <p>L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results</p> <p>Compliance</p> <p>UL Listed: Suitable for damp locations</p> <p>Enclosed Fixtures: Suitable for use in enclosed fixtures</p> <p>Certification Model Number: T10338(T8-15-U6GC-835-EXT)</p>	<p>DLC Listed: This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at designlights.org to confirm the qualification status of a specific SKU prior to specification or purchase.</p> <p>LED Characteristics</p> <p>Color Temperature: 3500K</p> <p>Color Accuracy (CRI): ≥80 CRI</p> <p>Beam Angle: 160°</p> <p>Construction</p> <p>Shape: U6</p>	<p>Endcap Material: Polycarbonate</p> <p>Enclosure Material: Glass & Polycarbonate</p> <p>Installation</p> <p>Base Type: G13</p> <p>Electrical</p> <p>THD: 20%</p> <p>Power Factor: 0.9</p> <p>Operating Temperature: -20°C to 45°C (-4°F to 113°F)</p> <p>Input Voltage: Driver Dependent</p> <p>Operating Frequency: 50/60Hz</p>

Technical Specifications (continued)

Dimming:

Yes with 0-10V dimmer. See Dimmer Compatibility List.

Other

5-Year, No-Compromise Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
24	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	17.1	10.6	17
PALLET	16	48.82	34.25	42.52

Dimension

