

Project: \_\_\_\_\_ Type: \_\_\_\_\_ Prepared By: \_\_\_\_\_ Date: \_\_\_\_\_



**Features and Benefits**

LEDs located on both sides of the tube provides 360-degree light output  
 Optics designed to deliver smooth even light without hot spots  
 Multiple lengths available for any application needed  
 120V-277V - Universal voltage  
 Ambient temperature: -20°C/-4°F to 55°C/131°F  
 Rotatable endcaps allow installer to direct light where needed  
 Robust plastic and aluminum construction to minimize breakage  
 Mercury and UV free. RoHS-compliant components.  
 Double-ended bypass installation for simple install and reduced maintenance costs

<b>Technical Specifications</b>		
<p><b>Performance</b></p> <hr/> <p><b>Product Type:</b> Linear</p> <p><b>Input Wattage:</b> 26W</p> <p><b>Lumens:</b> 3,500lm</p> <p><b>Efficacy:</b> 135lm/W</p> <p><b>L70 Lifespan:</b> 50,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations</p> <p><b>Wattage Equivalency:</b> T8HO and T12HO</p> <hr/> <p><b>LED Characteristics</b></p> <p><b>Color Accuracy (CRI):</b> 80</p> <p><b>Color Temperature:</b> 6500K</p>	<p><b>Beam Angle:</b> 360°</p> <hr/> <p><b>Electrical</b></p> <p><b>THD:</b> &lt;20%</p> <p><b>Power Factor:</b> &gt;0.9</p> <p><b>Dimmable:</b> Non-Dim</p> <p><b>Operating Temperature:</b> -20°C to 55°C</p> <p><b>Input Voltage:</b> 120-277V</p> <p><b>Operating Frequency:</b> 50/60Hz</p> <hr/> <p><b>Construction</b></p> <p><b>Nominal Length:</b> 64"</p>	<p><b>Shape:</b> T8</p> <hr/> <p><b>Enclosure Material:</b> Plastic+Aluminum</p> <p><b>Lens Finish:</b> Clear</p> <hr/> <p><b>Installation</b></p> <p><b>Base Type:</b> R17D</p> <p><b>Installation Method:</b> UL Type B, Ballast Bypass - Double Ended Wire</p> <hr/> <p><b>Other</b></p> <p><b>Technology EQ:</b> Fluorescent</p>

