

Photometric Test Report

Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2017

Prepared For

RAB Lighting Inc.

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, Gary.Xiao@rabweb.com

Prepared By

Deliver Co., Ltd.

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

Project Number

DLF2111105

Report Number

DLF2111105-7a

Test Date

2021/11/8

Issue Date

2021/11/11

Prepared By



Wangzun Zhu

Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

1.0 Test Summary

DLC Technical Requirements v5.1

Outdoor - Pole/Arm-Mounted Area and Roadway Luminaires				
Requirement Category	Test Method	Requirements		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	1000		40311
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Standard 105	Premium 120	151.3
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		266.5
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	20.00%	120V	2.22%
		20.00%	277V	4.68%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.9	120V	0.999
		0.9	277V	0.966
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	7 step	5029±355	5039
		4 step	5029±220	
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥70		84
Minimum R9 (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥-40		12
Minimum Rf (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥70		84
Minimum Rg (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥89		94
Minimum IES Rcs,h1 (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	-18%≤IES Rcs,h1≤+23%		-12%
Zonal Lumen Requirement (0°-90°) (Goniophotometer - Section 4.2)	IES LM-79-2008	100%		100.00%
Zonal Lumen Requirement (80°-90°) (Goniophotometer - Section 4.2)	IES LM-79-2008	≤10%		0.45%
Input Voltage (V)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		120
(Goniophotometer - Section 4.2)		Non-Worst Case		277
Input Current (A)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		2.225
(Goniophotometer - Section 4.2)		Non-Worst Case		0.957
Power (Input Wattage - W)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		266.5
(Goniophotometer - Section 4.2)		Non-Worst Case		256.1

2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2021/11/8	ALEDL5T	G1
2	Goniophotometer Test	2021/11/8	ALEDL5T	G1
3	THD and PF Test	2021/11/8	ALEDL5T	G1

Remark(If any)

- 1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.
- 2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.


3.0 Production Description

Luminaire Description: ALEDL5T

Description: 260W/36,000 lm @ 5000K

Electrical Specification: 120V-277V,50/60HZ

Photos of Luminaire Characteristics



4.0 LM-79 Measurement and Test Results

4.1 Integrating Sphere Test

Model No.	ALEDL5T	Sample ID.	G1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

Test Result

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
120.00	60	2.228	267.1	0.999
276.94	60	0.959	256.4	0.966


Test Result

CCT (K)	CRI	R9	Duv
5039	84	12	0.001

Rf	Rg	IES Rcs,h1
84	94	-12%

4.1 Integrating Sphere Test

Results




Spectral values

DominantWavelength 571.16 nm
Purity 0.092
PeakWavelength 455.74 nm
Radiant Power 88.45 W
Width50%:


Color Coordinates

Correlated Color Temperat 5039 K
x: 0.3442 u: 0.2103 u': 0.2103
y: 0.3529 v: 0.3234 v': 0.4852
CRI01 83.4 CRI09 12.1
CRI02 92.9 CRI10 81.8
CRI03 94.7 CRI11 80.0
CRI04 80.9 CRI12 62.6
CRI05 83.3 CRI13 86.6
CRI06 88.0 CRI14 97.8
CRI07 84.9 CRI15 78.2
CRI08 66.2 CRI16 73.8
ResultsCRI 84.3



PlanckDistance 1.0E-003

4.1 Integrating Sphere Test



Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.0

4.0 LM-79 Measurement and Test Results

4.2 Goniophotometer Test

Model No.	ALEDL5T	Sample ID.	G1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5° vertical intervals and 10° horizontal intervals.

Test Conditions

Condition	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
WORST CASE	119.94	60	2.225	266.5	0.999
NON-WORST CASE	277.02	60	0.957	256.1	0.966


Test Result

Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
40311	156.0	156.1	149.2	149.4	151.3


Zonal Lumen Requirement (0° - 90°)	Zonal Lumen Requirement (80° - 90°)	BUG rating
100.00%	0.45%	B5-U0-G4

4.2 Goniophotometer Test

Light Distrubtion Curve



Isolux Plot



4.2 Goniophotometer Test


Zonal Lumen Summary

γ	C0	C45	C90	C135	C180	C225	C270	C315
10	401.6	402.4	383.5	369.0	377.2	382.0	392.9	398.2
20	475.1	483.2	475.8	392.2	345.0	346.5	369.8	408.0
30	656.7	647.3	650.8	493.8	405.9	359.0	413.1	491.1
40	955.9	916.2	945.9	666.9	543.0	444.7	544.4	661.4
50	1344	1314	1344	976.8	809.5	616.2	816.2	953.5
60	1409	1467	1369	1362	1247	1016	1241	1383
70	466.1	574.4	381.3	932.0	1051	1325	1150	1071
80	15.82	26.89	16.57	38.65	31.60	132.9	35.47	43.43
90	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0
DEG	LUMINOUS INTENSITY: *10cd							

	Zonal (lm)		Total (lm)	Percent
0-10	376.53	0 - 10	376.53	0.93%
10-20	1121.12	0 - 20	1497.65	3.72%
20-30	2126.51	0 - 30	3624.16	8.99%
30-40	3796.69	0 - 40	7420.85	18.41%
40-50	6675.70	0 - 50	14096.55	34.97%
50-60	10612.17	0 - 60	24708.72	61.29%
60-70	11738.92	0 - 70	36447.64	90.42%
70-80	3684.11	0 - 80	40131.75	99.55%
80-90	179.66	0 - 90	40311.41	100.00%
90-100	0.00	0 - 100	40311.41	100.00%
100-110	0.00	0 - 110	40311.41	100.00%
110-120	0.00	0 - 120	40311.41	100.00%
120-130	0.00	0 - 130	40311.41	100.00%
130-140	0.00	0 - 140	40311.41	100.00%
140-150	0.00	0 - 150	40311.41	100.00%
150-160	0.00	0 - 160	40311.41	100.00%
160-170	0.00	0 - 170	40311.41	100.00%
170-180	0.00	0 - 180	40311.41	100.00%


4.2 Goniophotometer Test

LCS/BUG




	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	1972.4	N.A.	4.9
FM - Front-Medium (30-60)	11904.9	N.A.	29.5
FH - Front-High (60-80)	6957.3	N.A.	17.3
FVH - Front-Very High (80-90)	65.6	N.A.	0.2
BL - Back-Low (0-30)	1651.7	N.A.	4.1
BM - Back-Medium (30-60)	9179.7	N.A.	22.8
BH - Back-High (60-80)	8465.7	N.A.	21.0
BVH - Back-Very High (80-90)	114.0	N.A.	0.3
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	40311.3	N.A.	100.0
BUG Rating	B5-U0-G4		

Coefficients of Utilization



Isolines



4.2 Goniophotometer Test

	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	225	240	255	270	285	300	315	330	345	360
0	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83	4058.83
1	4063.73	4057.48	4051.49	4045.65	4040.96	4035.86	4030.24	4024.95	4021.7	4019.51	4018.88	4019.96	4043.52	4047.65	4051.14	4053.61	4056.53	4059.31	4061.19	4061.26	4059.82	4058.63	4055.7	4051.42	4063.73
2	4062.52	4052.86	4044.36	4036.88	4029.17	4021.16	4011.89	4002.43	3996.73	3994.07	3995.2	3998.93	4025.6	4033.14	4038.81	4044.2	4051.92	4058.5	4064.23	4065.82	4065.15	4063.13	4058.38	4053.15	4062.52
3	4061.08	4048.72	4038.34	4028.62	4016.16	4001.31	3986.39	3973.42	3967.85	3966.56	3969.57	3973.58	4004.25	4013.72	4021.47	4027.94	4039.02	4050.58	4059.95	4063.27	4064.69	4063.29	4058.54	4050.93	4061.08
4	4063.31	4050.4	4035.59	4017.24	3999.46	3976.77	3953.75	3937.58	3932.45	3934.67	3935.19	3941.46	3976.44	3988.2	3996.48	4006.26	4019.58	4035.53	4048.64	4054.3	4056.4	4057.9	4057.66	4051.55	4063.31
5	4060.13	4052.05	4038.2	4004.07	3974.57	3947.34	3915.68	3892.86	3887.42	3892.06	3899.94	3908.63	3947.01	3958.73	3965.78	3976.75	3993.75	4015.01	4031.65	4040.45	4044.38	4051.16	4053.05	4047.95	4060.13
6	4049.73	4047.94	4036.54	3997.11	3950.21	3912.99	3873.19	3845.58	3837.07	3843.71	3862.3	3882.86	3926.44	3933.47	3932.21	3940.39	3960.58	3989.48	4012.11	4022.47	4027.81	4040.76	4041.71	4036.77	4049.73
7	4035.85	4038.55	4031.31	3994.1	3932.63	3889.04	3843.05	3806.48	3787.34	3797.17	3829.97	3861.75	3904.73	3909.57	3902.88	3905.28	3930.99	3966.47	3993.96	4007.18	4016.17	4025.83	4024.42	4019.47	4035.85
8	4020.15	4029.21	4026.83	3995.82	3926.14	3874.04	3822.46	3776.02	3744.65	3752.35	3801.32	3828.95	3867.43	3873.87	3874.02	3873.9	3899.22	3941.09	3974.03	3993.33	4006.64	4008.04	4005.54	4001.52	4020.15
9	4010.89	4026.96	4030.05	4005.15	3936.63	3879.47	3821.3	3763.46	3714.17	3716.24	3766.61	3785.96	3820.1	3823.67	3834.7	3845.88	3867.49	3914.23	3952.45	3975.39	3998.77	3992.63	3987.16	3985.9	4010.89
10	4016.13	4039.07	4044.09	4023.51	3959.5	3899.57	3835.17	3763.77	3699.8	3690.24	3727.24	3741.17	3772.48	3769.78	3790.11	3820.36	3842.47	3886.87	3928.78	3957.95	3986.27	3982.4	3973.89	3980.32	4016.13
11	4037.7	4068.09	4073.27	4056.25	3995.06	3939.39	3873.27	3783.26	3699.88	3671.81	3684.48	3695.04	3723.62	3718.25	3738.14	3791.17	3816.83	3857.74	3904.99	3938.82	3970.73	3975.95	3967.66	3990.72	4037.7
12	4067.86	4109.43	4117.51	4098.91	4043.15	3992.23	3924.17	3817.44	3711.4	3660.41	3644.49	3649.07	3673.81	3663.58	3692.95	3759.5	3793.83	3831.97	3883.58	3922.71	3952.25	3969.42	3974.08	4012.02	4067.86
13	4109.84	4159.57	4174.04	4154.84	4111.53	4065.7	3998.38	3877.34	3739.23	3656.85	3608.13	3601.61	3622.3	3609.75	3647.01	3725.47	3767.1	3802.68	3859.6	3906.57	3935.26	3963.56	3990.65	4040.63	4109.84
14	4164.99	4221.04	4239.55	4220.58	4189.21	4151.21	4082.56	3945.73	3779.88	3662.1	3583.46	3561.39	3575.06	3559.18	3602.34	3687.58	3739.88	3773.09	3833.85	3886.36	3918.83	3962.68	4012.73	4080.19	4164.99
15	4230.5	4290.59	4317.98	4273.93	4237.8	4170.45	4023.65	3833.45	3679.24	3573.32	3530.24	3532.75	3510.43	3559.56	3651.49	3714.17	3744.57	3807.57	3866.16	3903.71	3965.41	4042.58	4131.67	4230.5	
16	4310.8	4376.55	4408.76	4388.76	4379.95	4347.25	4280.46	4121.79	3901.64	3710.66	3573.96	3507.88	3492.92	3468.53	3515.73	3613.33	3684.96	3713.8	3779.96	3842.17	3891.78	3973.68	4082.11	4194.45	4310.8
17	4402.21	4471.87	4507.29	4484.12	4475.8	4447.6	4385.23	4212.67	3973.45	3745.5	3584.49	3497.96	3464.04	3435.81	3478.23	3573.12	3656.2	3687.36	3755.25	3819.75	3885.01	3989.77	4129.92	4267.94	
18	4508.77	4581.34	4620.37	4595.23	4595.44	4563.54	4505.04	4323.92	4059.37	3800.51	3609.03	3501.23	3447.74	3414.66	3446.25	3532.21	3628.1	3660.44	3730.34	3800.1	3885.95	4010.95	4186.48	4353.45	4508.77
19	4625.04	4702.71	4735.64	4709.76	4715.63	4690.4	4635.49	4437.35	4147.87	3855.78	3641.72	3515.23	3443.98	3401.89	3419.15	3496.48	3596.39	3633.24	3710.22	3782.98	3892.53	4041.69	4254.05	4450.63	4625.04
20	4750.72	4832.87	4861.12	4832.5	4832.73	4809.06	4757.94	4545.93	4242.04	3921.66	3685.2	3536.67	3450.41	3397.7	3401.81	3464.7	3567.14	3611.59	3698.41	3775.73	3907.48	4079.87	4331.17	4554.08	4750.72
21	4888.66	4973.19	4997.88	4964.11	4977.63	4957.24	4907.83	4683.13	4349.6	4002.15	3740.77	3564.04	3466.83	3400.88	3392.71	3439.28	3539.94	3595.18	3694.83	3776.02	3931.04	4129.98	4414.16	4671.42	4888.66
22	5032.39	5123.44	5136.75	5094.93	5103.65	5094.2	5043.02	4796.26	4449.42	4076.16	3797.58	3602.42	3496.4	3412.2	3391.41	3420.64	3521.57	3587.25	3701.94	3786.66	3962.46	4187.65	4505.31	4794.42	5032.39
23	5189.49	5282.62	5295.53	5245.31	5257.88	5241.98	5191.1	4933.19	4566.74	4170.33	3868.44	3654.94	3536.45	3435.08	3394.41	3409.82	3513.22	3587.88	3719.18	3808.94	4002.9	4253.36	4603.71	4925.99	5189.49
24	5356.83	5450.55	5456.51	5400.78	5424.79	5415.36	5359.56	5078.78	4686.26	4260.55	3938.26	3714.49	3586.16	3470.84	3404.52	3407.51	3512.18	3599.78	3747.81	3843.3	4050.22	4326.55	4711.51	5071.28	5356.83
25	5530.06	5633.51	5628.6	5560.93	5576.09	5570.13	5514.86	5211.45	4807.03	4357.02	4018.68	3784.94	3648.23	3514.88	3423.78	3413.55	3519.7	3623.17	3787.7	3889.58	4108.33	4411.29	4828.52	5223.22	5530.06
26	5714.78	5823.44	5814.17	5744.27	5771.2	5767.35	5713.94	5393.49	4951.68	4472.79	4106.96	3863.62	3718.04	3568.63	3456.5	3428.95	3538.22	3659.13	3840.17	3944.22	4175.59	4499.54	4950.64	5385.03	5714.78
27	5913.52	6022.44	5996.45	5916.41	5938.26	5952.8	5902.27	5555.19	5086.51	4577.44	4197.11	3948.27	3795.29	3627.53	3498.86	3455.5	3569.34	3704.1	3901.35	4011.54	4251.11	4592.15	5081.45	5551.31	5913.52
28	6121.56	6229.35	6193.2	6104.31	6116.86	6128.74	6088.71	5729.25	5239.35	4700.23	4291.66	4034.02	3879.41	3693.86	3547.5	3433.83	3608.59	3757.14	3969.77	4080.36	4327.75	4691.74	5217.47	5732.05	6121.56
29	6334.46	6440.12	6380.7	6283.38	6304.93	6342.18	6306.06	5928.51	5389.97	4820.93	4386.77	4121.86	3969.04	3768	3603.01	3539.66	3661.29	3818.96	4047.24	4157.86	4410.96	4797.09	5360.01	5918.26	6334.46
30	6566.81	6671.27	6586.75	6473.35	6480.21	6539.55	6507.98	6110.3	5538.79	4938.12	4491.19	4216.62	4059.04	3849.06	3664.78	3589.85	3715.62	3888.09	4131.11	4244.17	4501.91	4911.21	5509.78	6117.37	6566.81
31	6809.26	6912.59	6807.94	6688.44	6702.26	6772.4	6754.75	6348.98	5725.46	5076.81	4596.06	4314.58	4157.96	3934.86	3729.71	3645.92	3775.31	3965.33	4223.48	4332.46	4594.81	5028.18	5665.42	6319.69	6809.26
32	7065.24	7163.05	7037.73	6902.3	6912.25	7011.42	7001.66	6573.86	5898.42	5205.17	4703.64	4417.21	4263.33	4026.64	3802.27	3709.57	3844.79	4052.11	4319.02	4432.62	4693.43	5152.02	5839.95	6521.9	7065.24
33	7326.69	7424.14	7279.91	7135.78	7131.18	7241.96	7237.5	6800.36	6097.78	5358.46	4824.74	4528.3	4370.85	4122.87	3880.48	3778.15	3918.16	4141.42	4417.06	4535.58	4801.81	5288.21	6027.6	6754.02	7326.69
34	7599.74	7694.86	7529.97	7381.39	7391.53	7524.14	7518.03	7071.88	6315.94	5523.32	4948.64	4650.1	4488.77	4225.78	3962.65	3850.48	4000.05	4240.36	4526.72	4647.4	4916.95	5435.64	6226.9	6997.99	7599.74
35	7880.31	7978.98	7793.45	7629	7618.12	7775.94	7774.86	7299.66	6517.59	5684.22	5083.7	4782.19	4614.1	4336.04	4054.19	3933.51	4086.43	4343.87	4646.43	4772.76	5044.37	5595.16	6393.81	7253.86	7880.31
36	8167.9	8272.16	8079.2	7909.58	7901.46	8064.39	8061.66	7576.97	6758.61	5875.5	5231.44	4922.37	4749.03	4456.71	4151.2	4020.97	4176.93	4454.2	4776.8	4905.56	5179.76	5766.11	6561.29	7517.9	8167.9
37	8478.28	8596	8372.96	8195	8188.79	8386.07	8388.66	7859.27	6983.04	6059.39	5381.62	5078.11	4897.71	4583.19	4255.12	4115.84	4278.16	4579.92	4924.05	5056.72	5324.51	5943.12	6841.89	7793.85	8478.28
38	8804.14	8926.74	8689.16	8498.31	8462.14	8682.54	8690.96	8134.33	7220.69	6252.07	5543.57	5240.55	5062.43	4722.51	43										

Page 13 of 17

Page 14 of 17

161	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
162	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
163	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
164	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
165	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
166	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
167	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
168	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
169	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
171	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
172	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
173	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
174	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
175	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
176	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
177	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
178	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
179	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

4.0 LM-79 Measurement and Test Results

4.3 THD and PF Test

Model No.	ALEDL5T	Sample ID.	G1
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

Test Results

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
120.00	60	2.228	267.1	0.999	2.22%
276.94	60	0.959	256.4	0.966	4.68%

5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2020/12/26	2021/12/25
DLF108	Auxiliary Lamp	2020/12/26	2021/12/25
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-derectional	2020/12/26	2021/12/25
DLF116	AC Power Source	2020/12/26	2021/12/25
DLF113	Power Meter	2020/12/26	2021/12/25
DLF112	Temperature Recorder	2020/12/26	2021/12/25
DLF114	Temperature & Humidity Datalogger	2020/12/26	2021/12/25
DLF101	Goniophotometer	2020/12/26	2021/12/25
DLF125	Standard Lamp Standard Lamp Type: 76.58 V, 6.7875 A, Tungsten, Omni-derectional	2020/12/26	2021/12/25
DLF104	AC Power Source	2020/12/26	2021/12/25
DLF507	DC Power Source	2020/12/26	2021/12/25
DLF102	Power Meter	2020/12/26	2021/12/25
DLF111	Temperature & Humidity Datalogger	2020/12/26	2021/12/25
DLF119	Power Meter	2020/12/26	2021/12/25
DLF031	Temperature data logger	2020/12/26	2021/12/25
DLF022	Digital power meter	2020/12/26	2021/12/25
DLF003	Temperature & Humidity Datalogger	2020/12/26	2021/12/25

***** End of Test Report*****