

Photometric Test Report

Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2017

Prepared For RAB Lighting Inc.

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, Gary.Xiao@rabweb.com

Prepared By

Deliver Co., Ltd.

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

Project Number

DLF2207109

Report Number

DLF2207109-14a


Test Date

2022/7/29

Issue Date


2022/7/30

Prepared By



Wangzun Zhu

Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

1.0 Test Summary

DLC Technical Requirements v5.1

Outdoor - Pole/Arm-Mounted Area and Roadway Luminaires				
Requirement Category	Test Method	Requirements		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	1000		11647
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Standard 105	Premium 120	141.5
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		82.3
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	20.00%	120V	2.22%
		20.00%	277V	6.98%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.9	120V	0.999
		0.9	277V	0.965
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	7 step	5029±355	4816
		4 step	5029±220	
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥70		81
Minimum R9 (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥-40		-2
Minimum Rf (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥70		83
Minimum Rg (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥89		95
Minimum IES Rcs,h1 (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	-18%≤IES Rcs,h1≤+23%		-13%
Zonal Lumen Requirement (0°-90°) (Goniophotometer - Section 4.2)	IES LM-79-2008	100%		100.00%
Zonal Lumen Requirement (80°-90°) (Goniophotometer - Section 4.2)	IES LM-79-2008	≤10%		0.39%
Input Voltage (V)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		120
(Goniophotometer - Section 4.2)		Non-Worst Case		277
Input Current (A)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		0.687
(Goniophotometer - Section 4.2)		Non-Worst Case		0.299
Power (Input Wattage - W)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		82.3
(Goniophotometer - Section 4.2)		Non-Worst Case		80.1

2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2022/7/29	ALEDS5T	N1
2	Goniophotometer Test	2022/7/29	ALEDS5T	N1
3	THD and PF Test	2022/7/29	ALEDS5T	N1

Remark(If any)

- 1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.
- 2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.


3.0 Production Description

Luminaire Description: ALEDS5T

Description: 80W @ 4000K

Electrical Specification: 120V-277V,50/60HZ

Photos of Luminaire Characteristics



4.0 LM-79 Measurement and Test Results

4.1 Integrating Sphere Test

Model No.	ALEDS5T	Sample ID.	N1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

Test Result

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
120.00	60	0.684	82.0	0.999
277.03	60	0.298	79.8	0.965


Test Result

CCT (K)	CRI	R9	Duv
4816	81	-2	0.0043

Rf	Rg	IES Rcs,h1
83	95	-13%

4.1 Integrating Sphere Test

Results




Spectral values

DominantWavelength 571.40 nm
Purity 0.152
PeakWavelength 450.90 nm
Radiant Power 26.72 W
Width50%:

Color Coordinates

Correlated Color Temperat 4816 K
x: 0.3517 u: 0.2105 u': 0.2105
y: 0.3656 v: 0.3282 v': 0.4923
CRI01 78.3 CRI09 -1.5
CRI02 87.2 CRI10 69.9
CRI03 93.8 CRI11 78.0
CRI04 79.6 CRI12 56.5
CRI05 78.8 CRI13 80.5
CRI06 82.1 CRI14 96.8
CRI07 86.7 CRI15 71.4
CRI08 63.7 CRI16 69.1
ResultsCRI 81.3



PlanckDistance 4.3E-003

4.1 Integrating Sphere Test







IES TM-30-18 Color Rendition Report

Source: DLF2207109-14a

Manufacturer: RAB Lighting Inc.

Date: 2022/7/29

Model: ALED5T



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.3517
 y 0.3656
 u' 0.2105
 v' 0.4923

CIE 13.3-1995
(CRI)
 R_a 81
 R_g -1

Colors are for visual orientation purposes only. Created with the ANSI/IES TM-30-18 Calculator Version 2.0

4.0 LM-79 Measurement and Test Results

4.2 Goniophotometer Test

Model No.	ALEDS5T	Sample ID.	N1
Opreate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric paramters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5° vertical intervals and 10° horizontal intervals.

Test Conditions

Condition	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
WORST CASE	120.03	60	0.687	82.3	0.998
NON-WROST CASE	277.01	60	0.299	80.1	0.966


Test Result

Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
11647	156.8	155.2	150.2	148.0	141.5


Zonal Lumen Requirement (0° - 90°)	Zonal Lumen Requirement (80° - 90°)	BUG rating
100.00%	0.39%	B3-U0-G2

4.2 Goniophotometer Test

Light Distrubtion Curve



Isolux Plot



4.2 Goniophotometer Test


Zonal Lumen Summary

γ	C0	C45	C90	C135	C180	C225	C270	C315
10	1407	1396	1387	1396	1407	1396	1387	1396
20	1463	1407	1452	1407	1463	1407	1452	1407
30	1723	1585	1679	1585	1723	1585	1679	1585
40	2254	1968	2112	1968	2254	1968	2112	1968
50	2807	2597	2890	2597	2807	2597	2890	2597
60	3590	3512	3662	3512	3590	3512	3662	3512
70	2317	3278	2571	3278	2317	3278	2571	3278
80	99.96	151.0	95.60	151.0	99.96	151.0	95.60	151.0
90	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0
DEG	LUMINOUS INTENSITY:cd							

	Zonal (lm)		Total (lm)	Percent
0-10	135.20	0 - 10	135.20	1.16%
10-20	397.54	0 - 20	532.74	4.57%
20-30	708.49	0 - 30	1241.23	10.66%
30-40	1162.81	0 - 40	2404.04	20.64%
40-50	1838.95	0 - 50	4242.99	36.43%
50-60	2812.68	0 - 60	7055.67	60.58%
60-70	3366.52	0 - 70	10422.19	89.49%
70-80	1179.38	0 - 80	11601.57	99.61%
80-90	45.20	0 - 90	11646.77	100.00%
90-100	0.00	0 - 100	11646.77	100.00%
100-110	0.00	0 - 110	11646.77	100.00%
110-120	0.00	0 - 120	11646.77	100.00%
120-130	0.00	0 - 130	11646.77	100.00%
130-140	0.00	0 - 140	11646.77	100.00%
140-150	0.00	0 - 150	11646.77	100.00%
150-160	0.00	0 - 160	11646.77	100.00%
160-170	0.00	0 - 170	11646.77	100.00%
170-180	0.00	0 - 180	11646.77	100.00%


4.2 Goniophotometer Test

LCS/BUG




	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	620.6	N.A.	5.3
FM - Front-Medium (30-60)	2907.2	N.A.	25.0
FH - Front-High (60-80)	2272.9	N.A.	19.5
FVH - Front-Very High (80-90)	22.6	N.A.	0.2
BL - Back-Low (0-30)	620.6	N.A.	5.3
BM - Back-Medium (30-60)	2907.2	N.A.	25.0
BH - Back-High (60-80)	2272.9	N.A.	19.5
BVH - Back-Very High (80-90)	22.6	N.A.	0.2
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	11646.6	N.A.	100.0
BUG Rating	B3-U0-G2		

Coefficients of Utilization



Isolines



4.2 Goniophotometer Test

	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	225	240	255	270	285	300	315	330	345	360
0	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26	1455.26
1	1453.31	1453.57	1453.52	1453.53	1454.35	1454.2	1454.39	1454.2	1454.35	1453.53	1453.52	1453.57	1453.31	1453.57	1453.52	1453.53	1454.35	1454.2	1454.39	1454.2	1454.35	1453.53	1453.52	1453.57	1453.31
2	1447.53	1447.47	1447.18	1447.16	1447.25	1447.91	1448.27	1447.91	1447.25	1447.16	1447.18	1447.47	1447.53	1447.47	1447.18	1447.16	1447.25	1447.91	1448.27	1447.91	1447.25	1447.16	1447.18	1447.47	1447.53
3	1445	1444.63	1442.58	1438.78	1439.64	1441.83	1443.56	1441.83	1439.64	1438.78	1442.58	1444.63	1445	1444.63	1442.58	1438.78	1439.64	1441.83	1443.56	1441.83	1439.64	1438.78	1442.58	1444.63	1445
4	1440.15	1438.65	1435.46	1434.12	1432.47	1435.12	1437.55	1435.12	1432.47	1434.12	1435.46	1438.65	1440.15	1438.65	1435.46	1434.12	1432.47	1435.12	1437.55	1435.12	1432.47	1434.12	1435.46	1438.65	1440.15
5	1432.95	1431.53	1428.46	1427.65	1426.41	1427.4	1430.88	1427.4	1426.41	1427.65	1428.46	1431.53	1432.95	1431.53	1428.46	1427.65	1426.41	1427.4	1430.88	1427.4	1426.41	1427.65	1428.46	1431.53	1432.95
6	1426.2	1423.78	1420.69	1420.94	1420.03	1417.59	1421.71	1417.59	1420.03	1420.94	1420.69	1423.78	1426.2	1423.78	1420.69	1420.94	1420.03	1417.59	1421.71	1417.59	1420.03	1420.94	1420.69	1423.78	1426.2
7	1422.15	1418.76	1414.27	1414.18	1411.12	1407.08	1411.81	1407.08	1411.12	1414.18	1414.27	1418.76	1422.15	1418.76	1414.27	1414.18	1411.12	1407.08	1411.81	1407.08	1411.12	1414.18	1414.27	1418.76	1422.15
8	1416.27	1412.98	1410.81	1406.54	1401.8	1395.91	1401.37	1395.91	1401.8	1406.54	1410.81	1412.98	1416.27	1412.98	1410.81	1406.54	1401.8	1395.91	1401.37	1395.91	1401.8	1406.54	1410.81	1412.98	1416.27
9	1410.97	1408	1405.97	1399.98	1393.47	1387.8	1393.75	1387.8	1393.47	1399.98	1405.97	1408	1410.97	1408	1405.97	1399.98	1393.47	1387.8	1393.75	1387.8	1393.47	1399.98	1405.97	1408	1410.97
10	1406.58	1403.15	1400.68	1395.6	1387.6	1381.19	1386.8	1381.19	1387.6	1395.6	1400.68	1403.15	1406.58	1403.15	1400.68	1395.6	1387.6	1381.19	1386.8	1381.19	1387.6	1395.6	1400.68	1403.15	1406.58
11	1403.18	1400.13	1396.97	1392.18	1383.48	1376.78	1381.72	1376.78	1383.48	1392.18	1396.97	1400.13	1403.18	1400.13	1396.97	1392.18	1383.48	1376.78	1381.72	1376.78	1383.48	1392.18	1396.97	1400.13	1403.18
12	1400.89	1396.33	1394.41	1389.07	1380.72	1374.39	1379.22	1374.39	1380.72	1389.07	1394.41	1396.33	1400.89	1396.33	1394.41	1389.07	1380.72	1374.39	1379.22	1374.39	1380.72	1389.07	1394.41	1396.33	1400.89
13	1403.21	1396.48	1392.18	1386.16	1379.87	1374.04	1379.94	1374.04	1379.87	1386.16	1392.18	1396.48	1403.21	1396.48	1392.18	1386.16	1379.87	1374.04	1379.94	1374.04	1379.87	1386.16	1392.18	1396.48	1403.21
14	1407.72	1399.46	1391.66	1385.11	1380.98	1376.99	1383.59	1376.99	1380.98	1385.11	1391.66	1399.46	1407.72	1399.46	1391.66	1385.11	1380.98	1376.99	1383.59	1376.99	1380.98	1385.11	1391.66	1399.46	1407.72
15	1413.83	1404.41	1394.61	1384.14	1383.57	1382.59	1390.23	1382.59	1383.57	1384.14	1394.61	1404.41	1413.83	1404.41	1394.61	1384.14	1383.57	1382.59	1390.23	1382.59	1383.57	1384.14	1394.61	1404.41	1413.83
16	1420.75	1410.92	1400.17	1383.75	1388.53	1392.15	1399.03	1392.15	1388.53	1383.75	1400.17	1410.92	1420.75	1410.92	1400.17	1383.75	1388.53	1392.15	1399.03	1392.15	1388.53	1383.75	1400.17	1410.92	1420.75
17	1429.15	1418.53	1406.22	1385.83	1396.01	1403.55	1410.06	1403.55	1396.01	1385.83	1406.22	1418.53	1429.15	1418.53	1406.22	1385.83	1396.01	1403.55	1410.06	1403.55	1396.01	1385.83	1406.22	1418.53	1429.15
18	1439.29	1427.56	1414.04	1390.86	1404.63	1416.41	1423.01	1416.41	1404.63	1390.86	1414.04	1427.56	1439.29	1427.56	1414.04	1390.86	1404.63	1416.41	1423.01	1416.41	1404.63	1390.86	1414.04	1427.56	1439.29
19	1450.31	1437.99	1422.81	1398.19	1414.42	1429.87	1436.7	1429.87	1414.42	1398.19	1422.81	1437.99	1450.31	1437.99	1422.81	1398.19	1414.42	1429.87	1436.7	1429.87	1414.42	1398.19	1422.81	1437.99	1450.31
20	1463.36	1450.49	1432.6	1407.38	1424.94	1445.2	1451.73	1445.2	1424.94	1407.38	1432.6	1450.49	1463.36	1450.49	1432.6	1407.38	1424.94	1445.2	1451.73	1445.2	1424.94	1407.38	1432.6	1450.49	1463.36
21	1478.44	1464.84	1443.83	1418.28	1435.61	1460.47	1467.43	1460.47	1435.61	1418.28	1443.83	1464.84	1478.44	1464.84	1443.83	1418.28	1435.61	1460.47	1467.43	1460.47	1435.61	1418.28	1443.83	1464.84	1478.44
22	1494.44	1480.66	1456.29	1430.76	1446.35	1476.82	1484.08	1476.82	1446.35	1430.76	1456.29	1480.66	1494.44	1480.66	1456.29	1430.76	1446.35	1476.82	1484.08	1476.82	1446.35	1430.76	1456.29	1480.66	1494.44
23	1513.19	1498.77	1469.76	1444.24	1458.94	1494.55	1502.74	1494.55	1458.94	1444.24	1469.76	1498.77	1513.19	1498.77	1469.76	1444.24	1458.94	1494.55	1502.74	1494.55	1458.94	1444.24	1469.76	1498.77	1513.19
24	1532.97	1518.84	1484	1459.41	1474.15	1514.3	1522.38	1514.3	1474.15	1459.41	1484	1518.84	1532.97	1518.84	1484	1459.41	1474.15	1514.3	1522.38	1514.3	1474.15	1459.41	1484	1518.84	1532.97
25	1556.34	1540.99	1500.23	1476.24	1492.13	1535.32	1545.09	1535.32	1492.13	1476.24	1500.23	1540.99	1556.34	1540.99	1500.23	1476.24	1492.13	1535.32	1545.09	1535.32	1492.13	1476.24	1500.23	1540.99	1556.34
26	1582.17	1565.18	1518.13	1494.71	1512.06	1558.94	1569.8	1558.94	1512.06	1494.71	1518.13	1565.18	1582.17	1565.18	1518.13	1494.71	1512.06	1558.94	1569.8	1558.94	1512.06	1494.71	1518.13	1565.18	1582.17
27	1610.88	1592.07	1538.13	1514.36	1533.85	1583.25	1594.76	1583.25	1533.85	1514.36	1538.13	1592.07	1610.88	1592.07	1538.13	1514.36	1533.85	1583.25	1594.76	1583.25	1533.85	1514.36	1538.13	1592.07	1610.88
28	1643.31	1622.07	1561.48	1535.77	1556.86	1609.09	1622.4	1609.09	1556.86	1535.77	1561.48	1622.07	1643.31	1622.07	1561.48	1535.77	1556.86	1609.09	1622.4	1609.09	1556.86	1535.77	1561.48	1622.07	1643.31
29	1680.71	1654.74	1586.93	1559.03	1581.7	1636.31	1649.95	1636.31	1581.7	1559.03	1586.93	1654.74	1680.71	1654.74	1586.93	1559.03	1581.7	1636.31	1649.95	1636.31	1581.7	1559.03	1586.93	1654.74	1680.71
30	1723.03	1692.01	1616.09	1584.57	1608.21	1665.21	1678.91	1665.21	1608.21	1584.57	1616.09	1692.01	1723.03	1692.01	1616.09	1584.57	1608.21	1665.21	1678.91	1665.21	1608.21	1584.57	1616.09	1692.01	1723.03
31	1769.09	1733.29	1647.71	1612.69	1636.5	1695.28	1711.86	1695.28	1636.5	1612.69	1647.71	1733.29	1769.09	1733.29	1647.71	1612.69	1636.5	1695.28	1711.86	1695.28	1636.5	1612.69	1647.71	1733.29	1769.09
32	1816.21	1776.97	1682.09	1643.14	1666.07	1727.45	1747.41	1727.45	1666.07	1643.14	1682.09	1776.97	1816.21	1776.97	1682.09	1643.14	1666.07	1727.45	1747.41	1727.45	1666.07	1643.14	1682.09	1776.97	1816.21
33	1868.25	1824.71	1719.96	1676.55	1698	1761.4	1785.04	1761.4	1698	1676.55	1719.96	1824.71	1868.25	1824.71	1719.96	1676.55	1698	1761.4	1785.04	1761.4	1698	1676.55	1719.96	1824.71	1868.25
34	1920.69	1873.37	1759.95	1711.41	1731.4	1797.78	1824.48	1797.78	1731.4	1711.41	1759.95	1873.37	1920.69	1873.37	1759.95	1711.41	1731.4	1797.78	1824.48	1797.78	1731.4	1711.41	1759.95	1873.37	1920.69
35	1978.1	1926.1	1803.09	1749.32	1767.34	1836.6	1867.39	1836.6	1767.34	1749.32	1803.09	1926.1	1978.1	1926.1	1803.09	1749.32	1767.34	1836.6	1867.39	1836.6	1767.34	1749.32	1803.09	1926.1	1978.1
36	2035.18	1981.01	1847.48	1789.25	1805.34	1876.6	1911.69	1876.6	1805.34	1789.25	1847.48	1981.01	2035.18	1981.01	1847.48	1789.25	1805.34	1876.6	1911.69	1876.6	1805.34	1789.25	1847.48	1981.01	2035.18
37	2089.58	2035.2	1894.06	1830.83	1844.58	1919.04	1957.43	1919.04	1844.58	1830.83	1894.06	2035.2	2089.58	2035.2	1894.06	1830.83	1844.58	1919.04	1957.43	1919.04	1844.58	1830.83	1894.06	2035.2	2089.58
38	2144.26	2089.7	1943.42	1874.54	1886.21	1963.5	2006.84	1963.5	1886.21	1874.54	1943.42	2089.7	2144.26	2089.7	1943.42	1874.54</									

Page 13 of 17

Page 14 of 17

161	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
162	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
163	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
164	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
165	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
166	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
167	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
168	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
169	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
171	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
172	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
173	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
174	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
175	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
176	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
177	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
178	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
179	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

4.0 LM-79 Measurement and Test Results

4.3 THD and PF Test

Model No.	ALEDS5T	Sample ID.	N1
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

Test Results

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
120.00	60	0.684	82.0	0.999	2.22%
277.03	60	0.298	79.8	0.965	6.98%

5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2021/12/26	2022/12/25
DLF108	Auxiliary Lamp	2021/12/26	2022/12/25
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-derectional	2021/12/26	2022/12/25
DLF116	AC Power Source	2021/12/26	2022/12/25
DLF113	Power Meter	2021/12/26	2022/12/25
DLF112	Temperature Recorder	2021/12/26	2022/12/25
DLF114	Temperature & Humidity Datalogger	2021/12/26	2022/12/25
DLF101	Goniophotometer	2021/12/26	2022/12/25
DLF125	Standard Lamp Standard Lamp Type: 76.58 V, 6.7875 A, Tungsten, Omni-derectional	2021/12/26	2022/12/25
DLF104	AC Power Source	2021/12/26	2022/12/25
DLF507	DC Power Source	2021/12/26	2022/12/25
DLF102	Power Meter	2021/12/26	2022/12/25
DLF111	Temperature & Humidity Datalogger	2021/12/26	2022/12/25
DLF119	Power Meter	2021/12/26	2022/12/25
DLF031	Temperature data logger	2021/12/26	2022/12/25
DLF022	Digital power meter	2021/12/26	2022/12/25
DLF003	Temperature & Humidity Datalogger	2021/12/26	2022/12/25

***** End of Test Report*****