

Photometric Test Report

Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2017

Prepared For

RAB Lighting Inc.

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, Gary.Xiao@rabweb.com

Prepared By

Deliver Co., Ltd.

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

Project Number

DLF2305110

Report Number

DLF2305110-11a


Test Date

2023/5/24

Issue Date


2023/5/25

Prepared By



Wangzun Zhu

Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

1.0 Test Summary

DLC Technical Requirements v5.1

Indoor - Linear Ambient - Direct Linear Ambient Luminaires				
Requirement Category	Test Method	Requirements		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	750		4713
Lumen/ft (Goniophotometer - Section 4.2)	IES LM-79-2008	≥375		1178
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Standard 115	Premium 130	143.2
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		32.9
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	20.00%	120V	8.09%
		20.00%	277V	10.32%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.9	120V	0.993
		0.9	277V	0.942
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	7 step	3465±245	3469
		4 step	3465±124	
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥80		84
Minimum R9 (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥0		13
Minimum Rf (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥70		85
Minimum Rg (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥89		98
Minimum IES Rcs,h1 (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	-12%≤IES Rcs,h1≤+23%		-11%
Zonal Lumen Requirement (0°-60°) (Goniophotometer - Section 4.2)	IES LM-79-2008	≥40%		72.78%
Corrected UGR (X=4H, Y=8H, 70/50/20%) (Goniophotometer - Section 4.2)	CIE 190-2010	<22		22.8
Input Voltage (V)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		120
(Goniophotometer - Section 4.2)		Non-Wrost Case		277
Input Current (A)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		0.276
(Goniophotometer - Section 4.2)		Non-Wrost Case		0.125
Power (Input Wattage - W)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Wrost Case		32.9
(Goniophotometer - Section 4.2)		Non-Wrost Case		32.7

2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2023/5/24	CW4/33W/3500K	K1
2	Goniophotometer Test	2023/5/24	CW4/33W/3500K	K1
3	THD and PF Test	2023/5/24	CW4/33W/3500K	K1

Remark(If any)

1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.


2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

3.0 Production Description

Luminaire Description: CW4/33W/3500K

Electrical Specification: 120V-277V,50/60HZ

Photos of Luminaire Characteristics



4.0 LM-79 Measurement and Test Results

4.1 Integrating Sphere Test

Model No.	CW4/33W/3500K	Sample ID.	K1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

Test Result

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
120.00	60	0.276	32.9	0.993
277.04	60	0.125	32.7	0.942


Test Result

CCT (K)	CRI	R9	Duv
3469	84	13	0.0023

Rf	Rg	IES Rcs,h1
85	98	-11%

4.1 Integrating Sphere Test

Results




Spectral values

DominantWavelength 582.02 nm
Purity 0.371
PeakWavelength 600.58 nm
Radiant Power 12.15 W
Width50%:

Color Coordinates

Correlated Color Temporal 3469 K
x: 0.4046 u: 0.2376 u': 0.2376
y: 0.3852 v: 0.3392 v': 0.5089
CRI01 82.7 CRI09 12.5
CRI02 90.4 CRI10 77.9
CRI03 95.8 CRI11 83.3
CRI04 83.2 CRI12 70.1
CRI05 83.2 CRI13 84.5
CRI06 87.7 CRI14 97.9
CRI07 84.4 CRI15 76.1
CRI08 63.5 CRI16 74.3
ResultsCRI 83.9



PlanckDistance 2.3E-003

4.1 Integrating Sphere Test


IES TM-30-18 Color Rendition Report

Source: DLF2305110-11a

Manufacturer: RAB Lighting Inc.

Date: 2023/5/24

Model: CW4/33W/3500K



Notes: This is a recommended method for displaying IES TM-30-18 information.

x 0.4046
 y 0.3852
 u' 0.2376
 v' 0.5089

CIE 13.3-1995
(CRI)

R_a 85
 R_g 18

4.1 Integrating Sphere Test

Spectral Distribution over Visible Wavelength							
WL (nm)	Radiant (Watts/nm)	WL (nm)	Radiant (Watts/nm)	WL (nm)	Radiant (Watts/nm)	WL (nm)	Radiant (Watts/nm)
380	9.67E-04	485	1.74E-02	590	7.25E-02	695	1.21E-02
385	9.55E-04	490	2.07E-02	595	7.39E-02	700	1.03E-02
390	9.51E-04	495	2.56E-02	600	7.45E-02	705	8.80E-03
395	9.23E-04	500	3.04E-02	605	7.42E-02	710	7.50E-03
400	8.69E-04	505	3.46E-02	610	7.29E-02	715	6.38E-03
405	9.33E-04	510	3.79E-02	615	7.09E-02	720	5.46E-03
410	1.10E-03	515	4.05E-02	620	6.79E-02	725	4.64E-03
415	1.68E-03	520	4.27E-02	625	6.44E-02	730	3.95E-03
420	2.94E-03	525	4.40E-02	630	6.02E-02	735	3.39E-03
425	5.42E-03	530	4.54E-02	635	5.58E-02	740	2.87E-03
430	9.93E-03	535	4.68E-02	640	5.10E-02	745	2.46E-03
435	1.77E-02	540	4.82E-02	645	4.61E-02	750	2.10E-03
440	3.29E-02	545	5.00E-02	650	4.15E-02	755	1.81E-03
445	5.93E-02	550	5.19E-02	655	3.69E-02	760	1.56E-03
450	6.92E-02	555	5.41E-02	660	3.26E-02	765	1.33E-03
455	4.64E-02	560	5.65E-02	665	2.86E-02	770	1.16E-03
460	3.30E-02	565	5.93E-02	670	2.50E-02	775	9.95E-04
465	2.66E-02	570	6.21E-02	675	2.18E-02	780	8.60E-04
470	1.87E-02	575	6.52E-02	680	1.89E-02		
475	1.52E-02	580	6.80E-02	685	1.63E-02		
480	1.55E-02	585	7.05E-02	690	1.40E-02		

4.0 LM-79 Measurement and Test Results

4.2 Goniophotometer Test

Model No.	CW4/33W/3500K	Sample ID.	K1
Opreate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric paramters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5° vertical intervals and 10° horizontal intervals.

Test Conditions

Condition	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
WROST CASE	120.06	60	0.276	32.9	0.993
NON-WROST CASE	277.00	60	0.125	32.7	0.942


Test Result

Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
4713	169.3	162.4	110.6	118.8	143.2


Zonal Lumen Requirement (0° - 60°)	UGR (X=4H, Y=8H, 70/50/20%)	Length(ft)	Lumen/ft
72.78%	22.8	4.00	1178

4.2 Goniophotometer Test

Light Distrubtion Curve



Isolux Plot



4.2 Goniophotometer Test

Zonal Lumen Summary

γ	C0	C45	C90	C135	C180	C225	C270	C315
10	1474	1480	1486	1480	1474	1480	1486	1480
20	1379	1400	1421	1400	1379	1400	1421	1400
30	1241	1278	1315	1278	1241	1278	1315	1278
40	1064	1112	1169	1112	1064	1112	1169	1112
50	865.5	914.0	974.4	914.0	865.5	914.0	974.4	914.0
60	654.6	691.6	738.6	691.6	654.6	691.6	738.6	691.6
70	436.9	453.2	467.4	453.2	436.9	453.2	467.4	453.2
80	232.7	220.0	182.5	220.0	232.7	220.0	182.5	220.0
90	86.35	58.32	1.072	58.32	86.35	58.32	1.072	58.32
100	69.26	46.65	1.886	46.65	69.26	46.65	1.886	46.65
110	63.96	44.22	6.617	44.22	63.96	44.22	6.617	44.22
120	58.91	41.32	11.89	41.32	58.91	41.32	11.89	41.32
130	52.37	37.75	16.83	37.75	52.37	37.75	16.83	37.75
140	45.01	34.33	20.90	34.33	45.01	34.33	20.90	34.33
150	38.24	31.18	22.84	31.18	38.24	31.18	22.84	31.18
160	32.21	27.46	21.31	27.46	32.21	27.46	21.31	27.46
170	28.07	23.19	19.24	23.19	28.07	23.19	19.24	23.19
180	18.61	20.73	21.61	20.73	18.61	20.73	21.61	20.73
DEG	LUMINOUS INTENSITY:cd							

UGR Table - Corrected

UGR Table - Corrected												
Reflectances												
Ceiling Cavity		70	70	50	50	30		70	70	50	50	30
Walls		50	30	50	30	30		50	30	50	30	30
Floor Cavity		20	20	20	20	20		20	20	20	20	20
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise					
X=2H	Y=2H	18.2	19.8	18.7	20.2	20.6	18.0	19.5	18.4	19.9	20.4	
	3H	20.0	21.4	20.4	21.8	22.3	19.9	21.3	20.4	21.7	22.2	
	4H	20.6	21.9	21.0	22.3	22.8	20.7	22.0	21.2	22.5	23.0	
	6H	20.9	22.1	21.4	22.6	23.1	21.4	22.6	21.9	23.1	23.6	
	8H	21.0	22.2	21.5	22.6	23.2	21.7	22.9	22.2	23.3	23.9	
	12H	21.0	22.1	21.5	22.6	23.2	21.9	23.1	22.4	23.5	24.1	
4H	2H	18.8	20.1	19.3	20.6	21.1	18.6	19.9	19.1	20.4	20.9	
	3H	20.8	21.9	21.3	22.4	22.9	20.7	21.9	21.2	22.3	22.9	
	4H	21.5	22.5	22.0	23.0	23.6	21.7	22.7	22.2	23.2	23.7	
	6H	22.0	22.8	22.5	23.4	23.9	22.5	23.4	23.0	23.9	24.5	
	8H	22.1	22.9	22.6	23.4	24.0	22.8	23.7	23.4	24.2	24.8	
	12H	22.1	22.9	22.7	23.4	24.0	23.2	23.9	23.7	24.5	25.1	
8H	4H	21.8	22.6	22.3	23.2	23.7	22.0	22.8	22.5	23.3	23.9	
	6H	22.4	23.1	23.0	23.7	24.2	22.9	23.6	23.5	24.2	24.8	
	8H	22.5	23.2	23.1	23.8	24.4	23.4	24.0	23.9	24.6	25.2	
	12H	22.7	23.2	23.2	23.8	24.4	23.8	24.4	24.4	24.9	25.6	
12H	4H	21.8	22.6	22.4	23.1	23.7	22.0	22.7	22.5	23.3	23.9	
	6H	22.5	23.1	23.1	23.6	24.3	23.0	23.6	23.6	24.2	24.8	
	8H	22.7	23.2	23.3	23.8	24.5	23.5	24.0	24.1	24.6	25.3	
Maximum UGR = 25.6												

4.2 Goniophotometer Test

ZONAL LUMEN SUMMARY

	Zonal (lm)		Total (lm)	Percent
0-10	142.55	0 - 10	142.55	3.02%
10-20	408.25	0 - 20	550.80	11.69%
20-30	619.64	0 - 30	1170.44	24.84%
30-40	751.48	0 - 40	1921.92	40.78%
40-50	786.11	0 - 50	2708.03	57.46%
50-60	721.86	0 - 60	3429.89	72.78%
60-70	568.68	0 - 70	3998.57	84.85%
70-80	349.44	0 - 80	4348.01	92.26%
80-90	130.49	0 - 90	4478.50	95.03%
90-100	48.22	0 - 100	4526.72	96.06%
100-110	43.25	0 - 110	4569.97	96.97%
110-120	39.10	0 - 120	4609.07	97.80%
120-130	33.52	0 - 130	4642.59	98.52%
130-140	26.98	0 - 140	4669.57	99.09%
140-150	20.18	0 - 150	4689.75	99.52%
150-160	13.48	0 - 160	4703.23	99.80%
160-170	7.21	0 - 170	4710.44	99.96%
170-180	2.10	0 - 180	4712.54	100.00%

4.2 Goniophotometer Test


COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
Rw	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	118	118	118	118	115	115	115	115	108	108	108	103	103	103	97	97	97	95
1	107	102	98	93	104	99	95	91	94	91	88	89	87	84	85	83	81	78
2	97	89	81	76	94	86	80	74	82	76	72	78	73	69	74	70	67	65
3	88	77	69	62	85	76	68	62	72	65	60	68	63	58	65	61	57	54
4	81	68	60	53	78	67	58	52	64	56	51	61	55	50	58	53	48	46
5	74	61	52	45	72	60	51	45	57	49	44	54	48	43	52	46	42	40
6	68	55	46	39	66	54	45	39	51	44	38	49	43	37	47	41	37	35
7	63	50	41	35	61	49	40	34	47	39	34	45	38	33	43	37	33	30
8	59	45	37	31	57	44	36	31	43	35	30	41	34	30	39	34	29	27
9	55	42	33	28	53	41	33	27	39	32	27	38	31	27	36	31	26	24
10	52	38	30	25	50	38	30	25	36	29	25	35	29	24	34	28	24	22

CONE OF LIGHT DIAGRAM



4.0 LM-79 Measurement and Test Results

4.3 THD and PF Test

Model No.	CW4/33W/3500K	Sample ID.	K1
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

Test Results

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
120.00	60	0.276	32.9	0.993	8.09%
277.04	60	0.125	32.7	0.942	10.32%

5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2022/12/24	2023/12/23
DLF108	Auxiliary Lamp	2022/12/24	2023/12/23
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-directional	2022/12/24	2023/12/23
DLF116	AC Power Source	2022/12/16	2023/12/15
DLF516	Power Meter	2022/12/16	2023/12/15
DLF112	Temperature Recorder	2022/12/28	2023/12/27
DLF114	Temperature & Humidity Datalogger	2022/12/28	2023/12/27
DLF101	Goniophotometer	2022/12/24	2023/12/23
DLF511	AC Power Source	2022/12/16	2023/12/15
DLF512	AC Power Source	2022/12/16	2023/12/15
DLF513	AC Power Source	2022/12/16	2023/12/15
DLF507	DC Power Source	2022/12/16	2023/12/15
DLF111	Temperature & Humidity Datalogger	2022/12/28	2023/12/27
DLF119	Power Meter	2022/12/16	2023/12/15
DLF031	Temperature data logger	2022/6/22	2023/6/21
DLF073	Power Analyzer	2022/6/22	2023/6/21
DLF003	Temperature & Humidity Datalogger	2022/6/22	2023/6/21

***** End of Test Report*****