

# Photometric Test Report

## Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2017

## Prepared For

**RAB Lighting Inc.**

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, Gary.Xiao@rabweb.com

## Prepared By

**Deliver Co., Ltd.**

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

## Project Number

**DLF2208102**

## Report Number

**DLF2208102-9a**

## Test Date

**2022/8/2**

## Issue Date

**2022/8/3**

## Prepared By



Wangzun Zhu

## Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

## 1.0 Test Summary

DLC Technical Requirements v5.1

Outdoor - Architectural Flood and Spot Luminaires				
Requirement Category	Test Method	Requirements		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	1000		2500
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Standard 105	Premium 120	145.4
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		17.2
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	20.00%	120V	5.05%
		20.00%	277V	6.92%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.9	120V	0.994
		0.9	277V	0.947
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	7 step	5029±355	4931
		4 step	5029±220	
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥70		84
Minimum R9 (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	-		11
Minimum Rf (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥70		84
Minimum Rg (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥89		96
Minimum IES Rcs,h1 (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	-18%≤IES Rcs,h1≤+23%		-12%
Zonal Lumen Requirement (0°-90°) (Goniophotometer - Section 4.2)	IES LM-79-2008	85%		100.00%
Input Voltage (V)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		277
(Goniophotometer - Section 4.2)		Non-Worst Case		120
Input Current (A)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		0.066
(Goniophotometer - Section 4.2)		Non-Worst Case		0.142
Power (Input Wattage - W)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		17.2
(Goniophotometer - Section 4.2)		Non-Worst Case		16.9

## 2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2022/8/2	FFLEDXS @ 18W / 5000K	I1
2	Goniophotometer Test	2022/8/2	FFLEDXS @ 18W / 5000K	I1
3	THD and PF Test	2022/8/2	FFLEDXS @ 18W / 5000K	I1

### Remark(If any)


- 1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.
- 2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

## 3.0 Production Description

**Luminaire Description:** FFLEDXS @ 18W / 5000K

**Electrical Specification:** 120V-277V,50/60HZ

### Photos of Luminaire Characteristics



## 4.0 LM-79 Measurement and Test Results

### 4.1 Integrating Sphere Test

Model No.	FFLEDXS @ 18W / 5000K	Sample ID.	I1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.4	Humidity (%RH)	54.0

#### Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ .

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within  $\pm 0.2$  percent under load.

The sample was measured using  $4\pi$  geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

#### Test Result

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
119.95	60	0.141	16.8	0.994
277.01	60	0.065	17.1	0.947


#### Test Result

CCT (K)	CRI	R9	Duv
4931	84	11	0.00085

Rf	Rg	IES Rcs,h1
84	96	-12%

## 4.1 Integrating Sphere Test

### Results




#### Spectral values

DominantWavelength 572.76 nm  
Purity 0.108  
PeakWavelength 451.90 nm  
Radiant Power 5.894 W  
Width50%:

#### Color Coordinates

Correlated Color Temperat 4931 K  
x: 0.3473 u: 0.2116 u': 0.2116  
y: 0.3551 v: 0.3244 v': 0.4867

CRI01	82.0	CRI09	10.5
CRI02	89.8	CRI10	75.4
CRI03	94.2	CRI11	81.4
CRI04	82.2	CRI12	57.8
CRI05	82.3	CRI13	84.4
CRI06	85.1	CRI14	97.2
CRI07	87.1	CRI15	76.3
CRI08	67.3	CRI16	72.7
ResultsCRI	83.7		



PlanckDistance 8.5E-004

## 4.1 Integrating Sphere Test


### IES TM-30-18 Color Rendition Report

Source: DLF2208102-9a

Manufacturer: RAB Lighting Inc.

Date: 2022/8/2

Model: FFLEDXS @ 18W / 5000K



Notes: This is a recommended method for displaying IES TM-30-18 information.

$x$  0.3473  
 $y$  0.3551  
 $u'$  0.2116  
 $v'$  0.4867

CIE 13.3-1995  
(CRI)

$R_a$  85  
 $R_g$  17

## 4.0 LM-79 Measurement and Test Results

### 4.2 Goniophotometer Test

Model No.	FFLEDXS @ 18W / 5000K	Sample ID.	I1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

#### Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ , measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within  $\pm 0.2$  percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at  $0.5^{\circ}$  vertical intervals and  $10^{\circ}$  horizontal intervals.

#### Test Conditions

Condition	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
WORST CASE	276.97	60	0.066	17.2	0.944
NON-WORST CASE	120.00	60	0.142	16.9	0.991

#### Test Result


Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
2500	115.0	150.7	90.1	110.1	145.4

Zonal Lumen Requirement  
( $0^{\circ}$ - $90^{\circ}$ )


100.00%

## 4.2 Goniophotometer Test

### Light Distrubtion Curve



### Isolux Plot





## 4.2 Goniophotometer Test

### Zonal Lumen Summary

γ	C0	C45	C90	C135	C180	C225	C270	C315
10	1073	1082	1081	1061	1061	1061	1081	1082
20	1061	1013	1020	1026	1075	1026	1020	1013
30	1022	987.3	936.9	990.2	964.2	990.2	936.9	987.3
40	597.7	870.1	816.5	830.1	701.4	830.1	816.5	870.1
50	334.6	490.7	652.1	574.5	444.5	574.5	652.1	490.7
60	55.90	225.7	443.1	305.7	59.45	305.7	443.1	225.7
70	1.145	11.50	217.4	26.23	18.16	26.23	217.4	11.50
80	0.0353	0.0477	42.00	6.516	5.703	6.516	42.00	0.0477
90	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0
DEG	LUMINOUS INTENSITY:cd							

	Zonal (lm)		Total (lm)	Percent
0-10	104.11	0 - 10	104.11	4.16%
10-20	298.40	0 - 20	402.51	16.10%
20-30	468.38	0 - 30	870.89	34.83%
30-40	546.98	0 - 40	1417.87	56.71%
40-50	517.56	0 - 50	1935.43	77.41%
50-60	363.14	0 - 60	2298.56	91.93%
60-70	159.53	0 - 70	2458.10	98.31%
70-80	39.17	0 - 80	2497.27	99.88%
80-90	3.03	0 - 90	2500.30	100.00%
90-100	0.00	0 - 100	2500.30	100.00%
100-110	0.00	0 - 110	2500.30	100.00%
110-120	0.00	0 - 120	2500.30	100.00%
120-130	0.00	0 - 130	2500.30	100.00%
130-140	0.00	0 - 140	2500.30	100.00%
140-150	0.00	0 - 150	2500.30	100.00%
150-160	0.00	0 - 160	2500.30	100.00%
160-170	0.00	0 - 170	2500.30	100.00%
170-180	0.00	0 - 180	2500.30	100.00%

## 4.2 Goniophotometer Test

### Axial Candela


DEG.	HOR.	DEG.	VERT.
90	0	90	0
85	3.73	85	0.03
75	116.07	75	0.05
65	329.26	65	7.62
55	551.41	55	179.92
47.5	698	47.5	480.63
42.5	780.24	42.5	553.35
37.5	849.4	37.5	651.65
33	904.02	33	787.67
29	946.01	29	1046.78
25.5	977.95	25.5	1078.06
22.5	1001.83	22.5	1072.19
19.5	1023.11	19.5	1058.93
17	1040.33	17	1050.24
15	1053.01	15	1051.41
13	1063.79	13	1057.2
11	1075.19	11	1066.43
9	1085.37	9	1079.43
7	1092.72	7	1091.82
5	1096.58	5	1097.27
3	1099.42	3	1098.39
1	1100.68	1	1102.37
0	1101.19	0	1101.19
-1	1100.68	-1	1099.97
-3	1099.42	-3	1093.59
-5	1096.58	-5	1081.54
-7	1092.72	-7	1068.62
-9	1085.37	-9	1062.94
-11	1075.19	-11	1060.97
-13	1063.79	-13	1062.98
-15	1053.01	-15	1066.8
-17	1040.33	-17	1072.33
-19.5	1023.11	-19.5	1074.5
-22.5	1001.83	-22.5	1072.32
-25.5	977.95	-25.5	1047.97
-29	946.01	-29	987.42
-33	904.02	-33	873.99
-37.5	849.4	-37.5	751.9
-42.5	780.24	-42.5	663.79
-47.5	698	-47.5	547.85
-55	551.41	-55	194.87
-65	329.26	-65	28.51
-75	116.07	-75	9.7
-85	3.73	-85	3.13
-90	0	-90	0

## 4.2 Goniophotometer Test

### Characteristics

NEMA Type	7 H x 6 V
Maximum Candela	1102.37
Maximum Candela Angle	0 H 1 V
Horizontal Beam Angle (50%)	110.1
Vertical Beam Angle (50%)	90
Horizontal Field Angle (10%)	151
Vertical Field Angle (10%)	119.1
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Beam Lumens	1974
Beam Efficiency	N.A.
Field Lumens	2437
Field Efficiency	N.A.
Spill Lumens	63
Luminaire Lumens	2500
Total Efficiency	N.A.
Total Luminaire Watts	17.2
Ballast Factor	1

### ISOCANDELA CURVES



## Axial Candela

	0	1	3	5	7	9	11	13	15	17	19.5	22.5	25.5	29	33	37.5	42.5	47.5	55	65	75	85	90
90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
85	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.04	0.04	0.04	0.04	0.05	0.05	0.05	0.05	0.06	0
75	0.05	0.05	0.05	0.05	0.05	0.06	0.06	0.06	0.06	0.06	0.07	0.07	0.06	0.05	0.08	0.08	0.07	0.18	0.1	0.52	0.15	0.16	0
65	7.62	7.78	8.09	8.23	8.33	8.32	8.18	7.88	8.08	8.54	8.87	8.54	8.01	9.45	11.26	8.23	7.45	14.24	6.11	10.2	1.95	0.24	0
55	179.92 *	181.5 *	184.67 *	183.39 *	182.48 *	180.4 *	177.25 *	175.13 *	173.55 *	172.07 *	169.49 *	164.77 *	158.62 *	156.37 *	143.57 *	133.64 *	125.29 *	117.62 *	75.32	48.47	10.4	0.38	0
47.5	480.63 *	481.09 *	481.19 *	480.22 *	478.24 *	474.57 *	470.38 *	466.32 *	459.01 *	450.85 *	434.26 *	432.55 *	419.65 *	374.78 *	359.02 *	355.53 *	269.41 *	247.53 *	197.88 *	94.98	24.17	0.75	0
42.5	553.35 *	553.54 *	553.21 *	551.89 *	549.55 *	546.33 *	543.76 *	543.11 *	536.25 *	528.07 *	518.02 *	510.8 *	501.29 *	483.12 *	453.16 *	435.03 *	391.81 *	324.72 *	279.85 *	133.43 *	37.42	1.05	0
37.5	651.65 *	652.78 *	653.47 *	652.07 *	649.81 *	643.27 *	640.48 *	636.17 *	629.6 *	621.71 *	610.28 *	607.39 *	587.73 *	565.65 *	553.71 *	551.35 *	467.43 *	402.9 *	345.15 *	177.99 *	50.17	1.37	0
33	787.67 *	796.19 *	805.73 *	806.87 *	796.59 *	790.8 *	803.74 *	811.12 *	795.88 *	761.27 *	750.21 *	776.46 *	774.37 *	682.83 *	667.49 *	673.45 *	599.78 *	475.95 *	399.87 *	225.19 *	62.92	1.73	0
29	1046.78 *	1047.52 *	1045.97 *	1042.95 *	1038.93 *	1028.76 *	1017.5 *	1003.19 *	995.36 *	982.27 *	950.4 *	915.34 *	921.86 *	870.17 *	770.98 *	770.84 *	702.4 *	537.36 *	449.3 *	259.98 *	73.41	2.08	0
25.5	1078.06 *	1077.03 *	1074.87 *	1072.68 *	1068.52 *	1059.44 *	1049.99 *	1040.61 *	1028.06 *	1012.49 *	994.24 *	976.71 *	950.01 *	907.87 *	855.41 *	827.26 *	733.72 *	596.19 *	490.61 *	282.66 *	81.2	2.37	0
22.5	1072.19 *	1070.84 *	1068.58 *	1066.78 *	1061.88 *	1054.1 *	1045.97 *	1036.71 *	1024.69 *	1011.67 *	995.06 *	975.5 *	949.56 *	914.82 *	876.73 *	829.32 *	747.83 *	636.25 *	522.5 *	298.01 *	87.41	2.6	0
19.5	1058.93 *	1057.63 *	1055.74 *	1054.69 *	1048.85 *	1042.1 *	1035.1 *	1025.21 *	1013.18 *	1000.61 *	986.81 *	967.33 *	942.56 *	910.14 *	876.64 *	828.37 *	752.23 *	657.27 *	530.99 *	309.94 *	93.22	2.82	0
17	1050.24 *	1049.43 *	1048.05 *	1046 *	1041.75 *	1035.93 *	1028.23 *	1018.83 *	1006.9 *	994.83 *	982.88 *	963.02 *	936.29 *	910.45 *	876.56 *	826.33 *	752.05 *	664.13 *	537.56 *	318.25 *	97.69	2.99	0
15	1051.41 *	1051.12 *	1049.89 *	1047.59 *	1044.02 *	1037.92 *	1029.14 *	1018.79 *	1007.53 *	997.55 *	983.31 *	961.34 *	937.7 *	914.08 *	877.1 *	824.63 *	750.11 *	670.79 *	542.32 *	323.31 *	100.95	3.11	0
13	1057.2 *	1057.24 *	1056.06 *	1053.75 *	1050.03 *	1043.71 *	1034.25 *	1022.95 *	1013.91 *	1002.66 *	986.27 *	965.37 *	945.51 *	918.79 *	878.53 *	822.88 *	754.79 *	676.91 *	546.81 *	326.95 *	103.93	3.23	0
11	1066.43 *	1066.64 *	1065.05 *	1063.18 *	1058.93 *	1052.13 *	1042.1 *	1033.32 *	1022.32 *	1009.37 *	993.07 *	975.02 *	953.55 *	923.95 *	880.31 *	825.08 *	760.33 *	682.51 *	549.58 *	329.66 *	106.62	3.51	0
9	1079.43 *	1079.91 *	1077.97 *	1075.41 *	1071.46 *	1063.96 *	1054.12 *	1044.12 *	1031.97 *	1018.94 *	1003.36 *	984.13 *	961.51 *	929 *	885.99 *	831.89 *	766.17 *	687.38 *	551.97 *	331.48 *	109.01	3.55	0
7	1091.82 *	1092.05 *	1089.84 *	1086.78 *	1082.71 *	1074.88 *	1065.28 *	1053.28 *	1041.16 *	1028.27 *	1012.43 *	992.37 *	968.39 *	934.83 *	891.67 *	838.44 *	771.11 *	691.52 *	553.49 *	332.42 *	111.11 *	3.59	0
5	1097.27 *	1096.95 *	1095.28 *	1092.19 *	1088.13 *	1080.78 *	1070.75 *	1058.66 *	1047.45 *	1035.52 *	1019.24 *	997.57 *	972.84 *	939.7 *	896.88 *	842.48 *	775.06 *	694.76 *	554.1 *	332.52 *	113.86 *	3.63	0
3	1098.39 *	1098.38 *	1096.72 *	1093.54 *	1090.87 *	1083.53 *	1072.26 *	1061.4 *	1051.01 *	1038.76 *	1021.82 *	1000.18 *	975.86 *	943.19 *	900.73 *	846.08 *	777.96 *	696.91 *	554.92 *	332.65 *	114.74 *	3.67	0
1	1102.37 *	1101.35 *	1100.06 *	1097.26 *	1093.06 *	1085.48 *	1075.04 *	1063.56 *	1052.93 *	1040.37 *	1023.02 *	1001.61 *	977.58 *	945.52 *	903.41 *	848.58 *	779.77 *	697.93 *	552.58 *	330.39 *	115.63 *	3.73	0
0	1101.19 *	1100.68 *	1099.42 *	1096.58 *	1092.72 *	1085.37 *	1075.19 *	1063.79 *	1053.01 *	1040.33 *	1023.11 *	1001.83 *	977.95 *	946.01 *	904.02 *	849.4 *	780.24 *	698 *	551.41 *	329.26 *	116.07 *	3.73	0
-1	1099.97 *	1098.97 *	1097.96 *	1095.1 *	1090.98 *	1083.55 *	1073.47 *	1062.07 *	1050.93 *	1037.86 *	1020.16 *	998.84 *	975.1 *	943.73 *	902.36 *	848.26 *	780.07 *	698.8 *	553.11 *	330.18 *	116.07 *	3.73	0
-3	1093.59 *	1093.01 *	1091.69 *	1088.87 *	1084.96 *	1076.87 *	1067.67 *	1056.6 *	1044.71 *	1031.05 *	1013.2 *	991.89 *	968.49 *	937.89 *	897.64 *	845.18 *	778.91 *	699.57 *	556.49 *	332.01 *	116.06 *	3.73	0
-5	1081.54 *	1081.99 *	1080.11 *	1077.64 *	1074.09 *	1066.03 *	1057.29 *	1046.9 *	1036.12 *	1022.88 *	1004.71 *	983.87 *	960.72 *	931.11 *	891.91 *	841.09 *	776.74 *	699.28 *	556.66 *	331.48 *	116.05 *	3.73	0
-7	1068.62 *	1069.04 *	1067.85 *	1065.78 *	1061.53 *	1055.96 *	1045.13 *	1034.86 *	1026.27 *	1015.25 *	998.94 *	976.59 *	951.78 *	923.32 *	885.08 *	836.67 *	773.65 *	698.06 *	556.99 *	330.98 *	114.14 *	3.73	0
-9	1062.94 *	1062.76 *	1061.59 *	1059.22 *	1055.68 *	1048.67 *	1040.27 *	1029.64 *	1017.33 *	1008.01 *	994.16 *	974.38 *	950.33 *	917.31 *	878.03 *	830.08 *	769.72 *	695.98 *	556.34 *	329.66 *	112.88 *	3.73	0
-11	1060.97 *	1060.64 *	1059.86 *	1057.36 *	1053.28 *	1046.8 *	1037.5 *	1028.08 *	1017.53 *	1005.02 *	989.69 *	972.5 *	950.39 *	919.69 *	874.6 *	823.48 *	765.09 *	693.14 *	554.71 *	327.49 *	111.3 *	3.73	0
-13	1062.98 *	1062.26 *	1061.27 *	1058.55 *	1055.12 *	1048.4 *	1038.81 *	1028.76 *	1018.97 *	1007.15 *	990.4 *	970.95 *	950.5 *	921.32 *	877.26 *	822.13 *	760.87 *	689.63 *	552.6 *	324.46 *	109.39	3.47	0
-15	1066.8 *	1065.84 *	1064.58 *	1062.12 *	1058.06 *	1052.13 *	1042.72 *	1032.38 *	1021.75 *	1010.24 *	993.85 *	972.56 *	950.92 *	922.51 *	879.08 *	824.27 *	755.78 *	685.21 *	548.59 *	320.55 *	107.17	3.38	0
-17	1072.33 *	1071.21 *	1069.5 *	1067.28 *	1061.77 *	1055.98 *	1046.88 *	1035.75 *	1024.92 *	1013.45 *	996.43 *	975.45 *	952.44 *	923.35 *	880.54 *	824.96 *	753.37 *	679.8 *	544.17 *	315.51 *	104.63	3.29	0
-19.5	1074.5 *	1073.68 *	1072.06 *	1070.5 *	1064.34 *	1057.28 *	1049.17 *	1038.24 *	1026.72 *	1014.33 *	999.1 *	977.14 *	952.14 *	921.8 *	881.45 *	823.32 *	747.25 *	667.58 *	537.34 *	307.69 *	100.99	3.15	0
-22.5	1072.32 *	1071.72 *	1070.15 *	1068.41 *	1062.16 *	1053.66 *	1045.12 *	1035.01 *	1021.31 *	1008.5 *	994.32 *	973.21 *	943.6 *	909.71 *	877 *	816.31 *	735.88 *	647.58 *	527.22 *	296.74 *	95.87	2.97	0
-25.5	1047.97 *	1048.15 *	1047.3 *	1045.08 *	1039.91 *	1031.35 *	1021.61 *	1011.75 *	999.37 *	985.61 *	970.07 *	952.41 *	922.52 *	885.43 *	846.78 *	802.27 *	715.02 *	621.74 *	500.77 *	283.49 *	89.91	2.76	0
-29	987.42 *	988.75 *	988.2 *	985.39 *	980.16 *	972.96 *	964.57 *	954.9 *	944.94 *	932.75 *	915.62 *	896.82 *	877.62 *	840.03 *	792.94 *	754.13 *	680.9 *	583.98 *	466.11 *	265.59 *	82.03	2.49	0
-33	873.99 *	876.19 *	876.78 *	874.33 *	868.4 *	863.99 *	858.21 *	852.36 *	843.24 *	830.67 *	817.12 *	804.19 *	786.02 *	750.93 *	714.78 *	680.69 *	620.26 *	531.35 *	424.71 *	241.16 *	72.2	2.15	0
-37.5	751.9 *	752.84 *	753.13 *	751.22 *	748.32 *	741.24 *	738.6 *	734.74 *	728.16 *	719.2 *	704.86 *	696.18 *	681.07 *	654.88 *	622.45 *	597.38 *	540.4 *	466.67 *	375.18 *	204.25 *	59.91	1.79	0
-42.5	663.79 *	664.01 *	663.58 *	662.02 *	659.35 *	655.46 *	651.07 *	647.37 *	639.25 *	631.41 *	620.75 *	610.13 *	592.1 *	566.41 *	539.57 *	511.91 *	454.18 *	392.29 *	311.02 *	157.43 *	45.35	1.46	0
-47.5	547.85 *	549.31 *	550.62 *	549.98 *	547.61 *	542.95 *	536.09 *	531.2 *	525.36 *	519.06 *	510.32 *	499.19 *	478.63 *	455.13 *	433.9 *	407.21 *	343.03 *	300.21 *	232.27 *	115.65 *	33	1.14	0
-55	194.87 *	197.75 *	203.52 *	203.44 *	203.28 *	200.87 *	196.07 *	193.93 *	197.97 *	199.45 *	197.1 *	187.65 *	176.12 *	181.58 *	180.89 *	159.67 *	140.16 *	142.17 *	90.6	67.37	15.62	0.73	0
-65	28.51	28.54	28.6	28.55	28.51	28.42	28.3	28.13	28.08	27.9	27.57	27.04	26.65	27.39	26.8	24.46	24.67	27.12	19.26	21.27	6.25	0.54	0
-75	9.7	9.72	9.76	9.81	9.74	9.71	9.66	9.59	9.53	9.51	9.42	9.24	9.04	8.77	8.69	8.23	7.57	7.54	6.42	4.66	2.02	0.42	0
-85	3.13	3.13	3.13	3.12	3.12	3.12	3.12	3.1	3.09	3.05	3.01	2.96	2.9	2.83	2.72	2.56	2.34	2.13	1.77	1.34	0.85	0.17	0
-90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0.01	0.01	0.01	0.01	0	0	0

## LUMEN TABULATION

	0	1	3	5	7	9	11	13	15	17	20	23	26	29	33	38	43	48	55	65	75	85	90	Total
90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
75	0	0	0	0	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0	0	0	0	0
65	0.3	0.6	0.6	0.6	0.6	0.6	0.6	0.5	0.5	0.7	0.8	0.7	0.8	0.8	0.8	0.8	0.7	0.8	0.5	0.2	0	0	0	0
55	0.76 *	1.52 *	1.51 *	1.50 *	1.49 *	1.47 *	1.44 *	1.41 *	1.38 *	1.66 *	1.92 *	1.84 *	1.97 *	2.02 *	2.08 *	1.93 *	1.53 *	1.71 *	1.2	0.4	0	0	0	0
47.5	0.79 *	1.57 *	1.57 *	1.56 *	1.54 *	1.53 *	1.51 *	1.48 *	1.45 *	1.75 *	2.02 *	1.95 *	2.11 *	2.18 *	2.24 *	2.12 *	1.66 *	1.88 *	1.34 *	0.4	0	0	0	0
42.5	0.92 *	1.84 *	1.83 *	1.82 *	1.80 *	1.78 *	1.76 *	1.73 *	1.70 *	2.06 *	2.40 *	2.30 *	2.53 *	2.68 *	2.79 *	2.69 *	2.14 *	2.42 *	1.78 *	0.5	0.1	0	0	0
37.5	0.99 *	1.99 *	2.00 *	1.98 *	1.95 *	1.94 *	1.94 *	1.91 *	1.85 *	2.23 *	2.63 *	2.58 *	2.78 *	2.90 *	3.08 *	3.01 *	2.36 *	2.61 *	1.96 *	0.60 *	0.1	0	0	0
33	1.12 *	2.25 *	2.25 *	2.23 *	2.21 *	2.18 *	2.17 *	2.13 *	2.07 *	2.49 *	2.89 *	2.83 *	3.08 *	3.12 *	3.23 *	3.20 *	2.49 *	2.66 *	2.03 *	0.65 *	0.1	0	0	0
29	1.13 *	2.26 *	2.25 *	2.24 *	2.21 *	2.18 *	2.14 *	2.10 *	2.06 *	2.49 *	2.86 *	2.75 *	3.03 *	3.11 *	3.16 *	3.10 *	2.42 *	2.59 *	1.97 *	0.63 *	0.1	0	0	0
25.5	0.98 *	1.96 *	1.95 *	1.94 *	1.92 *	1.89 *	1.87 *	1.83 *	1.79 *	2.18 *	2.52 *	2.41 *	2.65 *	2.78 *	2.84 *	2.75 *	2.19 *	2.41 *	1.82 *	0.58 *	0.1	0	0	0
22.5	0.97 *	1.94 *	1.94 *	1.92 *	1.90 *	1.88 *	1.85 *	1.82 *	1.78 *	2.17 *	2.51 *	2.40 *	2.64 *	2.80 *	2.86 *	2.76 *	2.26 *	2.52 *	1.90 *	0.62 *	0.1	0	0	0
19.5	0.80 *	1.60 *	1.60 *	1.59 *	1.57 *	1.55 *	1.53 *	1.50 *	1.47 *	1.79 *	2.08 *	1.99 *	2.19 *	2.33 *	2.38 *	2.30 *	1.90 *	2.13 *	1.61 *	0.53 *	0.1	0	0	0
17	0.64 *	1.28 *	1.27 *	1.27 *	1.25 *	1.24 *	1.22 *	1.20 *	1.17 *	1.43 *	1.66 *	1.59 *	1.75 *	1.87 *	1.91 *	1.84 *	1.53 *	1.73 *	1.31 *	0.44 *	0.1	0	0	0
15	0.64 *	1.28 *	1.28 *	1.27 *	1.26 *	1.24 *	1.22 *	1.20 *	1.18 *	1.44 *	1.66 *	1.59 *	1.76 *	1.87 *	1.90 *	1.84 *	1.54 *	1.74 *	1.32 *	0.44 *	0.1	0	0	0
13	0.65 *	1.29 *	1.29 *	1.28 *	1.27 *	1.25 *	1.23 *	1.21 *	1.19 *	1.44 *	1.67 *	1.60 *	1.77 *	1.88 *	1.91 *	1.84 *	1.55 *	1.75 *	1.33 *	0.45 *	0.1	0	0	0
11	0.65 *	1.31 *	1.30 *	1.29 *	1.28 *	1.26 *	1.24 *	1.22 *	1.20 *	1.46 *	1.69 *	1.62 *	1.79 *	1.89 *	1.92 *	1.86 *	1.56 *	1.77 *	1.34 *	0.46 *	0.1	0	0	0
9	0.66 *	1.32 *	1.32 *	1.31 *	1.29 *	1.28 *	1.26 *	1.23 *	1.21 *	1.47 *	1.70 *	1.63 *	1.80 *	1.90 *	1.93 *	1.87 *	1.57 *	1.78 *	1.35 *	0.46 *	0.1	0	0	0
7	0.67 *	1.33 *	1.33 *	1.32 *	1.31 *	1.29 *	1.27 *	1.24 *	1.22 *	1.48 *	1.72 *	1.64 *	1.81 *	1.91 *	1.94 *	1.88 *	1.58 *	1.78 *	1.35 *	0.46 *	0.1	0	0	0
5	0.67 *	1.34 *	1.33 *	1.32 *	1.31 *	1.29 *	1.27 *	1.25 *	1.22 *	1.49 *	1.72 *	1.65 *	1.82 *	1.92 *	1.95 *	1.89 *	1.59 *	1.79 *	1.35 *	0.46 *	0.1	0	0	0
3	0.67 *	1.34 *	1.33 *	1.33 *	1.31 *	1.29 *	1.27 *	1.25 *	1.22 *	1.49 *	1.73 *	1.65 *	1.82 *	1.93 *	1.96 *	1.90 *	1.59 *	1.79 *	1.35 *	0.46 *	0.1	0	0	0
1	0.34 *	0.67 *	0.67 *	0.66 *	0.66 *	0.65 *	0.64 *	0.63 *	0.61 *	0.75 *	0.86 *	0.83 *	0.91 *	0.97 *	0.98 *	0.95 *	0.80 *	0.89 *	0.67 *	0.23 *	0	0	0	0
0	0.34 *	0.67 *	0.67 *	0.66 *	0.66 *	0.65 *	0.64 *	0.63 *	0.61 *	0.75 *	0.86 *	0.83 *	0.91 *	0.96 *	0.98 *	0.95 *	0.80 *	0.89 *	0.67 *	0.23 *	0	0	0	0

-1	0.67 *	1.33 *	1.33 *	1.32 *	1.31 *	1.29 *	1.27 *	1.25 *	1.22 *	1.48 *	1.72 *	1.64 *	1.81 *	1.92 *	1.95 *	1.90 *	1.59 *	1.79 *	1.35 *	0.47 *	0.1	0	0
-3	0.66 *	1.32 *	1.32 *	1.31 *	1.30 *	1.28 *	1.26 *	1.24 *	1.21 *	1.47 *	1.70 *	1.63 *	1.80 *	1.91 *	1.94 *	1.89 *	1.59 *	1.79 *	1.35 *	0.47 *	0.1	0	0
-5	0.66 *	1.31 *	1.30 *	1.30 *	1.28 *	1.27 *	1.25 *	1.22 *	1.20 *	1.46 *	1.69 *	1.62 *	1.78 *	1.90 *	1.93 *	1.88 *	1.59 *	1.79 *	1.35 *	0.46 *	0.1	0	0
-7	0.65 *	1.30 *	1.29 *	1.29 *	1.27 *	1.26 *	1.24 *	1.21 *	1.19 *	1.45 *	1.68 *	1.61 *	1.77 *	1.88 *	1.92 *	1.87 *	1.58 *	1.79 *	1.35 *	0.46 *	0.1	0	0
-9	0.65 *	1.29 *	1.29 *	1.28 *	1.27 *	1.25 *	1.23 *	1.21 *	1.19 *	1.45 *	1.68 *	1.61 *	1.77 *	1.87 *	1.91 *	1.86 *	1.57 *	1.79 *	1.34 *	0.46 *	0.1	0	0
-11	0.65 *	1.29 *	1.29 *	1.28 *	1.27 *	1.25 *	1.23 *	1.21 *	1.19 *	1.44 *	1.67 *	1.60 *	1.77 *	1.88 *	1.90 *	1.85 *	1.57 *	1.78 *	1.34 *	0.45 *	0.1	0	0
-13	0.65 *	1.29 *	1.29 *	1.28 *	1.27 *	1.25 *	1.23 *	1.21 *	1.19 *	1.45 *	1.68 *	1.60 *	1.77 *	1.88 *	1.90 *	1.84 *	1.56 *	1.77 *	1.33 *	0.45 *	0.1	0	0
-15	0.65 *	1.30 *	1.30 *	1.29 *	1.28 *	1.26 *	1.24 *	1.22 *	1.19 *	1.45 *	1.68 *	1.61 *	1.78 *	1.88 *	1.91 *	1.84 *	1.55 *	1.76 *	1.31 *	0.44 *	0.1	0	0
-17	0.82 *	1.63 *	1.63 *	1.61 *	1.60 *	1.58 *	1.55 *	1.52 *	1.49 *	1.82 *	2.10 *	2.01 *	2.22 *	2.35 *	2.39 *	2.30 *	1.92 *	2.17 *	1.62 *	0.54 *	0.1	0	0
-20	0.98 *	1.96 *	1.95 *	1.94 *	1.92 *	1.89 *	1.86 *	1.83 *	1.79 *	2.18 *	2.52 *	2.41 *	2.65 *	2.81 *	2.85 *	2.73 *	2.26 *	2.55 *	1.90 *	0.63 *	0.1	0	0
-23	0.97 *	1.93 *	1.93 *	1.92 *	1.89 *	1.87 *	1.84 *	1.80 *	1.76 *	2.15 *	2.49 *	2.37 *	2.60 *	2.76 *	2.81 *	2.69 *	2.20 *	2.46 *	1.83 *	0.60 *	0.1	0	0
-26	1.09 *	2.17 *	2.16 *	2.15 *	2.12 *	2.09 *	2.06 *	2.02 *	1.98 *	2.41 *	2.79 *	2.67 *	2.92 *	3.07 *	3.13 *	3.01 *	2.45 *	2.72 *	2.02 *	0.66 *	0.1	0	0
-29	1.14 *	2.27 *	2.26 *	2.25 *	2.22 *	2.20 *	2.16 *	2.13 *	2.08 *	2.53 *	2.93 *	2.81 *	3.08 *	3.24 *	3.29 *	3.19 *	2.60 *	2.87 *	2.13 *	0.69 *	0.1	0	0
-33	1.12 *	2.23 *	2.23 *	2.21 *	2.19 *	2.16 *	2.13 *	2.10 *	2.06 *	2.50 *	2.90 *	2.79 *	3.06 *	3.22 *	3.29 *	3.20 *	2.61 *	2.89 *	2.13 *	0.68 *	0.1	0	0
-38	1.08 *	2.16 *	2.15 *	2.14 *	2.11 *	2.09 *	2.06 *	2.03 *	1.99 *	2.42 *	2.81 *	2.69 *	2.95 *	3.11 *	3.18 *	3.07 *	2.49 *	2.76 *	1.99 *	0.61 *	0.1	0	0
-43	0.92 *	1.85 *	1.84 *	1.83 *	1.81 *	1.79 *	1.76 *	1.73 *	1.69 *	2.06 *	2.39 *	2.27 *	2.48 *	2.60 *	2.65 *	2.50 *	2.00 *	2.21 *	1.55 *	0.5	0.1	0	0
-48	0.85 *	1.71 *	1.72 *	1.71 *	1.69 *	1.66 *	1.63 *	1.61 *	1.58 *	1.93 *	2.23 *	2.10 *	2.29 *	2.45 *	2.48 *	2.30 *	1.87 *	2.05 *	1.44 *	0.5	0.1	0	0
-55	0.34 *	0.70 *	0.71 *	0.70 *	0.70 *	0.68 *	0.67 *	0.66 *	0.66 *	0.82 *	0.9	0.9	1	1.1	1.1	1	0.9	1	0.8	0.3	0	0	0
-65	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0	0	0
-75	0	0	0	0	0	0	0	0	0	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0	0	0	0
-85	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
-90	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Total	29.3	58.6	58.4	58.1	57.5	56.7	55.9	54.9	53.7	65.3	75.7	72.5	79.7	84	85.7	82.7	68	75.9	56.6	18.6	2.3	0.01	1250

## 4.0 LM-79 Measurement and Test Results

### 4.3 THD and PF Test

Model No.	FFLEDXS @ 18W / 5000K	Sample ID.	I1
Temperature (°C)	25.4	Humidity (%RH)	54.0

#### Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at  $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ . The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

#### Test Results

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
119.95	60	0.141	16.8	0.994	5.05%
277.01	60	0.065	17.1	0.947	6.92%

## 5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2021/12/26	2022/12/25
DLF108	Auxiliary Lamp	2021/12/26	2022/12/25
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-derectional	2021/12/26	2022/12/25
DLF116	AC Power Source	2021/12/26	2022/12/25
DLF113	Power Meter	2021/12/26	2022/12/25
DLF112	Temperature Recorder	2021/12/26	2022/12/25
DLF114	Temperature & Humidity Datalogger	2021/12/26	2022/12/25
DLF101	Goniophotometer	2021/12/26	2022/12/25
DLF125	Standard Lamp Standard Lamp Type: 76.58 V, 6.7875 A, Tungsten, Omni-derectional	2021/12/26	2022/12/25
DLF104	AC Power Source	2021/12/26	2022/12/25
DLF507	DC Power Source	2021/12/26	2022/12/25
DLF102	Power Meter	2021/12/26	2022/12/25
DLF111	Temperature & Humidity Datalogger	2021/12/26	2022/12/25
DLF119	Power Meter	2021/12/26	2022/12/25
DLF031	Temperature data logger	2021/12/26	2022/12/25
DLF022	Digital power meter	2021/12/26	2022/12/25
DLF003	Temperature & Humidity Datalogger	2021/12/26	2022/12/25

\*\*\*\*\* End of Test Report\*\*\*\*\*