

Photometric Test Report

Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2014

Prepared For RAB Lighting Inc.

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, Gary.Xiao@rabweb.com

Prepared By

Deliver Co., Ltd.

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

Project Number

DLF2404111

Report Number

DLF2404111-22a

Test Date

2024/4/22

Issue Date


2024/4/23

Prepared By



Wangzun Zhu

Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

1.0 Test Summary

DLC Technical Requirements v5.1

Indoor - High Bay Luminaires (Commercial and Industrial)				
Requirement Category	Test Method	Requirements		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	10000		17350
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Standard 120	Premium 135	142.7
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		121.6
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	20.00%		12.87%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.9		0.915
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	7 step	3045±175	3062
		4 step	3045±100	
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥70		80
Minimum R9 (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥-40		-3
Minimum Rf (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥70		83
Minimum Rg (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥89		95
Minimum IES Rcs,h1 (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	-18%≤IES Rcs,h1≤+23%		-13%
Zonal Lumen Requirement (20°-50°) (Goniophotometer - Section 4.2)	IES LM-79-2008	≥30%		65.80%
Corrected UGR (X=4H, Y=8H, 70/50/20%) (Goniophotometer - Section 4.2)	CIE 190-2010	<28		25.6
Input Voltage (V)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		480
Input Current (A)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		0.277
Power (Input Wattage - W)				
(Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		121.6

2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2024/4/22	H15B/480 @ 120W/3000K	V1
2	Goniophotometer Test	2024/4/22	H15B/480 @ 120W/3000K	V1
3	THD and PF Test	2024/4/22	H15B/480 @ 120W/3000K	V1

Remark(If any)


- 1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.
- 2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

3.0 Production Description

Luminaire Description: H15B/480 @ 120W/3000K

Electrical Specification: 480V,50/60HZ

Photos of Luminaire Characteristics



4.0 LM-79 Measurement and Test Results

4.1 Integrating Sphere Test

Model No.	H15B/480 @ 120W/3000K	Sample ID.	V1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

Test Result



Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
480.00	60	0.276	121.4	0.915

Test Result

CCT (K)	CRI	R9	Duv
3062	80	-3	0.0002

Rf	Rg	IES Rcs,h1
83	95	-13%

4.1 Integrating Sphere Test



4.1 Integrating Sphere Test







IES TM-30-18 Color Rendition Report

Source: DLF2404111-22a

Manufacturer: RAB Lighting Inc.

Date: 2024/4/22

Model: H15B/480 @ 120W/3000K



Notes: This is a recommended method for displaying IES TM-30-18 information.

x 0.4323
 y 0.4023
 u' 0.2484
 v' 0.5200

CIE 13.3-1995
(CRI)

R_a 81
 R_g 2

4.1 Integrating Sphere Test

Spectral Distribution over Visible Wavelength							
WL (nm)	Radiant (Watts/nm)	WL (nm)	Radiant (Watts/nm)	WL (nm)	Radiant (Watts/nm)	WL (nm)	Radiant (Watts/nm)
380	3.76E-04	485	5.89E-02	590	3.15E-01	695	5.20E-02
385	3.46E-04	490	6.48E-02	595	3.24E-01	700	4.48E-02
390	3.76E-04	495	7.69E-02	600	3.24E-01	705	3.81E-02
395	4.17E-04	500	9.17E-02	605	3.23E-01	710	3.26E-02
400	5.65E-04	505	1.09E-01	610	3.17E-01	715	2.78E-02
405	1.02E-03	510	1.26E-01	615	3.08E-01	720	2.38E-02
410	2.20E-03	515	1.38E-01	620	2.93E-01	725	2.03E-02
415	4.54E-03	520	1.50E-01	625	2.77E-01	730	1.72E-02
420	8.66E-03	525	1.60E-01	630	2.58E-01	735	1.47E-02
425	1.56E-02	530	1.68E-01	635	2.37E-01	740	1.25E-02
430	2.64E-02	535	1.75E-01	640	2.17E-01	745	1.07E-02
435	4.33E-02	540	1.85E-01	645	1.97E-01	750	9.02E-03
440	6.91E-02	545	1.92E-01	650	1.76E-01	755	7.68E-03
445	1.11E-01	550	2.03E-01	655	1.57E-01	760	6.74E-03
450	1.66E-01	555	2.14E-01	660	1.39E-01	765	5.65E-03
455	1.79E-01	560	2.28E-01	665	1.23E-01	770	4.79E-03
460	1.45E-01	565	2.44E-01	670	1.07E-01	775	4.06E-03
465	1.13E-01	570	2.59E-01	675	9.36E-02	780	3.43E-03
470	9.04E-02	575	2.76E-01	680	8.13E-02		
475	7.06E-02	580	2.91E-01	685	7.05E-02		
480	5.99E-02	585	3.05E-01	690	6.06E-02		

4.0 LM-79 Measurement and Test Results

4.2 Goniophotometer Test

Model No.	H15B/480 @ 120W/3000K	Sample ID.	V1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5° vertical intervals and 10° horizontal intervals.

Test Conditions

Condition	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
WORST CASE	479.98	60	0.277	121.6	0.915


Test Result

Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
17350	125.6	122.1	87.3	88.0	142.7


Zonal Lumen Requirement (20°-50°)	UGR (X=4H, Y=8H, 70/50/20%)
65.80%	25.6

4.2 Goniophotometer Test

Light Distrubtion Curve



Isolux Plot



4.2 Goniophotometer Test

Zonal Lumen Summary

γ	C0	C45	C90	C135	C180	C225	C270	C315
10	8945	8973	8937	8973	8945	8973	8937	8973
20	8551	8580	8555	8580	8551	8580	8555	8580
30	7795	7862	7813	7862	7795	7862	7813	7862
40	5873	5916	5975	5916	5873	5916	5975	5916
50	2599	2621	2617	2621	2599	2621	2617	2621
60	1190	1116	1008	1116	1190	1116	1008	1116
70	443.5	422.8	389.4	422.8	443.5	422.8	389.4	422.8
80	137.3	134.3	132.0	134.3	137.3	134.3	132.0	134.3
90	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0
170	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0
DEG	LUMINOUS INTENSITY:cd							

UGR Table - Corrected

UGR Table - Corrected										
Reflectances										
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30
Walls	50	30	50	30	30	50	30	50	30	30
Floor Cavity	20	20	20	20	20	20	20	20	20	20
Room Size										
UGR Viewed Crosswise										
X=2H Y=2H	24.3	25.6	24.6	25.9	26.2	23.9	25.3	24.3	25.6	25.9
3H	24.8	26.0	25.2	26.3	26.7	24.6	25.8	25.0	26.1	26.5
4H	25.0	26.1	25.4	26.4	26.8	24.8	25.9	25.2	26.2	26.6
6H	25.1	26.1	25.5	26.4	26.8	24.9	25.9	25.3	26.3	26.7
8H	25.1	26.0	25.5	26.4	26.8	24.9	25.9	25.3	26.3	26.7
12H	25.1	26.0	25.5	26.4	26.8	24.9	25.8	25.3	26.2	26.6
UGR Viewed Endwise										
4H 2H	24.5	25.6	24.9	25.9	26.3	24.2	25.3	24.6	25.6	26.0
3H	25.2	26.1	25.6	26.5	26.9	24.9	25.9	25.4	26.3	26.7
4H	25.4	26.2	25.8	26.6	27.1	25.2	26.0	25.6	26.4	26.9
6H	25.6	26.3	26.0	26.7	27.2	25.4	26.1	25.8	26.5	27.0
8H	25.6	26.2	26.1	26.7	27.2	25.4	26.1	25.9	26.5	27.0
12H	25.6	26.2	26.1	26.7	27.1	25.4	26.0	25.9	26.5	27.0
UGR Viewed Endwise										
8H 4H	25.4	26.1	25.9	26.5	27.0	25.2	25.9	25.7	26.3	26.8
6H	25.6	26.2	26.1	26.7	27.1	25.5	26.0	26.0	26.5	27.0
8H	25.7	26.2	26.2	26.7	27.2	25.5	26.0	26.0	26.5	27.0
12H	25.7	26.2	26.3	26.7	27.2	25.6	26.0	26.1	26.5	27.1
UGR Viewed Endwise										
12H 4H	25.4	26.0	25.9	26.5	26.9	25.2	25.8	25.7	26.3	26.7
6H	25.6	26.1	26.1	26.6	27.1	25.4	25.9	26.0	26.4	26.9
8H	25.7	26.1	26.2	26.6	27.2	25.5	26.0	26.1	26.5	27.0
Maximum UGR = 27.2										

4.2 Goniophotometer Test

ZONAL LUMEN SUMMARY

	Zonal (lm)		Total (lm)	Percent
0-10	861.58	0 - 10	861.58	4.97%
10-20	2482.11	0 - 20	3343.69	19.27%
20-30	3807.91	0 - 30	7151.60	41.22%
30-40	4409.60	0 - 40	11561.20	66.63%
40-50	3199.79	0 - 50	14760.99	85.08%
50-60	1558.54	0 - 60	16319.53	94.06%
60-70	698.83	0 - 70	17018.36	98.09%
70-80	268.56	0 - 80	17286.92	99.64%
80-90	63.30	0 - 90	17350.22	100.00%
90-100	0.00	0 - 100	17350.22	100.00%
100-110	0.00	0 - 110	17350.22	100.00%
110-120	0.00	0 - 120	17350.22	100.00%
120-130	0.00	0 - 130	17350.22	100.00%
130-140	0.00	0 - 140	17350.22	100.00%
140-150	0.00	0 - 150	17350.22	100.00%
150-160	0.00	0 - 160	17350.22	100.00%
160-170	0.00	0 - 170	17350.22	100.00%
170-180	0.00	0 - 180	17350.22	100.00%

4.2 Goniophotometer Test

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
R/W	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	89
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	84	81	79
3	96	88	82	76	94	87	81	76	84	79	74	81	77	73	79	75	72	70
4	90	80	73	67	88	79	72	67	76	70	66	74	69	65	72	68	64	62
5	84	73	65	60	82	72	65	59	70	64	59	68	62	58	66	61	58	56
6	78	66	59	53	76	66	58	53	64	58	53	62	57	52	61	56	52	50
7	73	61	53	48	71	60	53	48	59	52	48	57	52	47	56	51	47	45
8	68	56	49	44	67	56	48	43	54	48	43	53	47	43	52	47	43	41
9	64	52	45	40	63	51	44	40	50	44	39	49	43	39	48	43	39	37
10	60	48	41	36	59	48	41	36	47	41	36	46	40	36	45	40	36	34

CONE OF LIGHT DIAGRAM



4.0 LM-79 Measurement and Test Results

4.3 THD and PF Test

Model No.	H15B/480 @ 120W/3000K	Sample ID.	V1
Temperature (°C)	25.3	Humidity (%RH)	56.0

Test Method

The samples were tested according to the ANSI C82.77:2014.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

Test Results

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
480.00	60	0.276	121.4	0.915	12.87%

5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2023/12/24	2024/12/23
DLF108	Auxiliary Lamp	2023/12/24	2024/12/23
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-directional	2023/12/24	2024/12/23
DLF116	AC Power Source	2023/12/16	2024/12/15
DLF516	Power Meter	2023/12/16	2024/12/15
DLF112	Temperature Recorder	2023/12/28	2024/12/27
DLF114	Temperature & Humidity Datalogger	2023/12/28	2024/12/27
DLF101	Goniophotometer	2023/12/24	2024/12/23
DLF511	AC Power Source	2023/12/16	2024/12/15
DLF512	AC Power Source	2023/12/16	2024/12/15
DLF513	AC Power Source	2023/12/16	2024/12/15
DLF507	DC Power Source	2023/12/16	2024/12/15
DLF111	Temperature & Humidity Datalogger	2023/12/28	2024/12/27
DLF119	Power Meter	2023/12/16	2024/12/15
DLF031	Temperature data logger	2023/6/22	2024/6/21
DLF073	Power Analyzer	2023/6/22	2024/6/21
DLF003	Temperature & Humidity Datalogger	2023/6/22	2024/6/21

***** End of Test Report*****