

Photometric Test Report

Relevant Standards

- ☒ IES LM-79-2008
- ☒ ANSI C82.77:2017

Prepared For

RAB Lighting Inc.

Room 6A33, No.1388, Wuzhong road, Shanghai, China

Xiao Xiang, 15921313292, Gary.Xiao@rabweb.com

Prepared By

Deliver Co., Ltd.

Block 11, 78 Keling Road, SSTP, Suzhou, China

0512-66801950, kevin.jia@szdeliver.com

Project Number

DLF2211104

Report Number

DLF2211104-1a

Test Date

2022/11/23

Issue Date


2022/11/29

Prepared By



Wangzun Zhu

Approved By



Kevin Jia

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of Deliver Co., Ltd.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP.

1.0 Test Summary

DLC Technical Requirements v5.1

Indoor - Linear Ambient - Direct Linear Ambient Luminaires				
Requirement Category	Test Method	Requirements		Test value
Luminaire Output (lm) (Goniophotometer - Section 4.2)	IES LM-79-2008	-		164
Lumen/ft (Goniophotometer - Section 4.2)	IES LM-79-2008	≥ 375		257
Minimum Luminaire Efficacy (lm/W) (Goniophotometer - Section 4.2)	IES LM-79-2008	-		65.8
Power (Input Wattage) (W) (Goniophotometer - Section 4.2)	IES LM-79-2008	Worst Case		2.5
Total Harmonic Distortion (A%) (THD & PF - section 4.3)	ANSI C82.77:2014	20.00%		7.90%
Power Factor (THD & PF - section 4.3)	ANSI C82.77:2014	0.9		0.980
Allowable CCTs* (K) (Integrating Sphere - Section 4.1)	IES LM-79-2008	7 step	2725 \pm 145	2660
		4 step	2725 \pm 83	
Minimum CRI (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥ 80		94
Minimum R9 (Integrating Sphere - Section 4.1)	IES LM-79-2008 CIE 13.3-1995	≥ 0		66
Minimum Rf (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥ 70		92
Minimum Rg (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	≥ 89		97
Minimum IES Rcs,h1 (Integrating Sphere - Section 4.1)	ANSI/IES TM-30-18	-12% \leq IES Rcs,h1 \leq +23%		-4%
Zonal Lumen Requirement (0°-60°) (Goniophotometer - Section 4.2)	IES LM-79-2008	$\geq 40\%$		79.35%
Corrected UGR (X=4H, Y=8H, 70/50/20%) (Goniophotometer - Section 4.2)	CIE 190-2010	<22		23.1

2.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2022/11/23	KNOOKFA8 / 2W / 2700K	A1
2	Goniophotometer Test	2022/11/23	KNOOKFA8 / 2W / 2700K	A1
3	THD and PF Test	2022/11/23	KNOOKFA8 / 2W / 2700K	A1

Remark(If any)

- 1、 This report shall not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the US government.
- 2、 The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.

3.0 Production Description

Luminaire Description: KNOOKFA8 / 2W / 2700K

Electrical Specification: 120V,50/60HZ

Photos of Luminaire Characteristics



4.0 LM-79 Measurement and Test Results

4.1 Integrating Sphere Test

Model No.	KNOOKFA8 / 2W / 2700K	Sample ID.	A1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	55.4

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$.

The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.

Test Result

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
119.95	60	0.021	2.5	0.980


Test Result

CCT (K)	CRI	R9	Duv
2660	94	66	0.0028

Rf	Rg	IES Rcs,h1
92	97	-4%

4.1 Integrating Sphere Test

Results




Spectral values

DominantWavelength	583.56 nm
Purity	0.666
PeakWavelength	629.21 nm
Radiant Power	0.5195 W
Width@50%	

Color Coordinates

Correlated Color Temperat		2660 K
x: 0.4681	u: 0.2635	u': 0.2635
y: 0.4201	v: 0.3548	v': 0.5321
CRI01	93.7	CRI09
CRI02	96.0	CRI10
CRI03	97.3	CRI11
CRI04	94.3	CRI12
CRI05	93.0	CRI13
CRI06	96.0	CRI14
CRI07	94.1	CRI15
CRI08	84.8	CRI16
ResultsCRI	93.6	



PlanckDistance 2.8E-003

4.1 Integrating Sphere Test


IES TM-30-18 Color Rendition Report

Source: DLF2211104-1a

Manufacturer: RAB Lighting Inc.

Date: 2022/11/23

Model: KNOOKFA8 / 2W / 2700K



Notes: This is a recommended method for displaying IES TM-30-18 information.

x 0.4681
 y 0.4201
 u' 0.2635
 v' 0.5321

CIE 13.3-1995
(CRI)

R_a 94
 R_g 68

4.0 LM-79 Measurement and Test Results

4.2 Goniophotometer Test

Model No.	KNOOKFA8 / 2W / 2700K	Sample ID.	A1
Operate time (Min.)	90	Stabilization time (Min.)	45
Temperature (°C)	25.3	Humidity (%RH)	54.0

Test Method

The samples were tested according to the IES LM-79-2008.

Photometric parameters were measured using a type C goniophotometer and software.

The ambient temperature shall be maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$, measured at a point not more than 1 m from the sample and at the same height as the sample.

The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5° vertical intervals and 10° horizontal intervals.

Test Conditions

Condition	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
WORST CASE	120.05	60	0.021	2.5	0.980


Test Result

Flux (lm)	Field Angle(10%)		Beam Angle(50%)		Luminous Efficacy (lm/W)
	C0-180	C90-270	C0-180	C90-270	
164	159.5	160.1	110.1	111.3	65.8


Zonal Lumen Requirement (0° - 60°)	UGR (X=4H, Y=8H, 70/50/20%)	Length(ft)	Lumen/ft
79.35%	23.1	0.64	257

4.2 Goniophotometer Test

Light Distrubtion Curve



Isolux Plot



4.2 Goniophotometer Test

Zonal Lumen Summary

γ	C0	C45	C90	C135	C180	C225	C270	C315
10	57.84	57.98	58.01	57.90	57.76	57.64	57.68	57.73
20	54.45	54.74	54.90	54.66	54.35	54.17	54.20	54.26
30	49.09	49.53	49.82	49.47	49.00	48.80	48.87	48.91
40	42.10	42.73	43.14	42.73	42.17	41.93	41.99	41.94
50	33.77	34.55	35.14	34.79	34.19	33.90	33.87	33.65
60	24.36	25.26	26.11	25.90	25.35	24.98	24.75	24.33
70	14.23	15.23	16.24	16.37	15.93	15.46	14.96	14.31
80	4.656	5.517	6.483	6.921	6.665	6.135	5.456	4.814
90	0.0169	0.0893	0.1692	0.2830	0.2043	0.1360	0.1256	0.1100
100	0.0135	0.0335	0.0419	0.0253	0.0098	0.0680	0.1304	0.0726
110	0.0182	0.0315	0.0430	0.0184	0.0171	0.0186	0.0594	0.0206
120	0.0244	0.0348	0.0430	0.0255	0.0238	0.0246	0.0253	0.0251
130	0.0310	0.0386	0.0446	0.0299	0.0350	0.0368	0.0375	0.0382
140	0.0375	0.0421	0.0457	0.0381	0.0502	0.0510	0.0517	0.0530
150	0.0419	0.0452	0.0466	0.0432	0.0541	0.0544	0.0550	0.0559
160	0.0452	0.0472	0.0481	0.0459	0.0548	0.0548	0.0550	0.0559
170	0.0488	0.0492	0.0492	0.0490	0.0548	0.0557	0.0557	0.0561
180	0.0546	0.0541	0.0530	0.0535	0.0559	0.0536	0.0537	0.0539
DEG	LUMINOUS INTENSITY:cd							

UGR Table - Corrected

UGR Table - Corrected

Reflectances											
Ceiling Cavity	70	70	50	50	30	70	70	50	50	30	
Walls	50	30	50	30	30	50	30	50	30	30	
Floor Cavity	20	20	20	20	20	20	20	20	20	20	
Room Size		UGR Viewed Crosswise					UGR Viewed Endwise				
X=2H	Y=2H	18.9	20.5	19.3	20.8	21.2	18.7	20.3	19.1	20.7	21.0
	3H	20.7	22.1	21.1	22.5	22.9	20.5	22.0	20.9	22.3	22.7
	4H	21.4	22.7	21.8	23.1	23.5	21.2	22.6	21.7	23.0	23.4
	6H	21.8	23.1	22.3	23.5	23.9	21.7	23.0	22.2	23.4	23.8
	8H	21.9	23.2	22.4	23.6	24.0	21.9	23.1	22.3	23.5	23.9
	12H	22.0	23.2	22.5	23.6	24.0	22.0	23.1	22.4	23.5	24.0
4H	2H	19.5	20.9	19.9	21.2	21.6	19.4	20.7	19.8	21.1	21.5
	3H	21.5	22.7	22.0	23.1	23.5	21.4	22.6	21.9	23.0	23.4
	4H	22.3	23.4	22.8	23.8	24.2	22.2	23.3	22.7	23.7	24.2
	6H	22.9	23.8	23.4	24.3	24.7	22.9	23.8	23.3	24.2	24.7
	8H	23.1	23.9	23.6	24.4	24.9	23.1	23.9	23.5	24.4	24.8
	12H	23.2	24.0	23.7	24.4	24.9	23.2	23.9	23.7	24.4	24.9
8H	4H	22.6	23.4	23.1	23.9	24.4	22.5	23.4	23.0	23.8	24.3
	6H	23.3	24.0	23.8	24.5	25.0	23.3	24.0	23.8	24.5	25.0
	8H	23.6	24.2	24.1	24.7	25.2	23.6	24.2	24.1	24.7	25.2
	12H	23.7	24.3	24.2	24.8	25.4	23.8	24.3	24.3	24.8	25.4
12H	4H	22.6	23.4	23.1	23.9	24.4	22.6	23.3	23.1	23.8	24.3
	6H	23.4	24.0	23.9	24.5	25.0	23.4	24.0	23.9	24.5	25.0
	8H	23.6	24.2	24.1	24.7	25.3	23.7	24.2	24.2	24.7	25.3

Maximum UGR = 25.4

4.2 Goniophotometer Test

ZONAL LUMEN SUMMARY

	Zonal (lm)		Total (lm)	Percent
0-10	5.57	0 - 10	5.57	3.39%
10-20	15.91	0 - 20	21.48	13.07%
20-30	23.98	0 - 30	45.46	27.65%
30-40	28.74	0 - 40	74.20	45.14%
40-50	29.63	0 - 50	103.83	63.16%
50-60	26.61	0 - 60	130.44	79.35%
60-70	20.05	0 - 70	150.49	91.54%
70-80	11.05	0 - 80	161.54	98.27%
80-90	2.59	0 - 90	164.13	99.84%
90-100	0.07	0 - 100	164.20	99.88%
100-110	0.04	0 - 110	164.24	99.91%
110-120	0.02	0 - 120	164.26	99.92%
120-130	0.03	0 - 130	164.29	99.94%
130-140	0.03	0 - 140	164.32	99.96%
140-150	0.03	0 - 150	164.35	99.98%
150-160	0.02	0 - 160	164.37	99.99%
160-170	0.01	0 - 170	164.38	99.99%
170-180	0.01	0 - 180	164.39	100.00%

4.2 Goniophotometer Test


COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Coefficients Of Utilization - Zonal Cavity Method

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
Rw/	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	117	117	117	117	111	111	111	107	107	107	102	102	102	100
1	109	104	100	96	106	102	98	95	98	95	92	94	91	89	90	88	86	84
2	99	91	84	78	97	89	83	77	85	80	76	82	78	74	79	75	72	70
3	90	80	72	65	88	78	71	65	75	69	63	72	67	62	70	65	61	59
4	83	71	62	55	80	69	61	55	67	60	54	65	58	53	62	57	53	50
5	76	63	54	48	74	62	54	47	60	52	47	58	51	46	56	50	46	44
6	70	57	48	42	68	56	47	41	54	47	41	52	46	41	51	45	40	38
7	65	52	43	37	63	51	42	37	49	42	36	48	41	36	46	40	36	34
8	61	47	39	33	59	46	38	33	45	38	32	44	37	32	43	36	32	30
9	57	43	35	29	55	43	35	29	41	34	29	40	34	29	39	33	29	27
10	53	40	32	27	52	39	32	27	38	31	26	37	31	26	36	31	26	24

CONE OF LIGHT DIAGRAM



4.0 LM-79 Measurement and Test Results

4.3 THD and PF Test

Model No.	KNOOKFA8 / 2W / 2700K	Sample ID.	A1
Temperature (°C)	25.3	Humidity (%RH)	55.4

Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

Test Results

Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
119.95	60	0.021	2.5	0.980	7.90%

5.0 Equipment Information

Test Equipment			
Equipment ID	Equipment Name	Last Calibration Date	Calibration Due Date
DLF107	Integrating Sphere System	2021/12/26	2022/12/25
DLF108	Auxiliary Lamp	2021/12/26	2022/12/25
DLF122	Measurement Standard Lamp Standard Lamp Type: 220 V, 0.4720 A, Tungsten, Omni-derectional	2021/12/26	2022/12/25
DLF116	AC Power Source	2021/12/26	2022/12/25
DLF113	Power Meter	2021/12/26	2022/12/25
DLF112	Temperature Recorder	2021/12/26	2022/12/25
DLF114	Temperature & Humidity Datalogger	2021/12/26	2022/12/25
DLF101	Goniophotometer	2021/12/26	2022/12/25
DLF125	Standard Lamp Standard Lamp Type: 76.58 V, 6.7875 A, Tungsten, Omni-derectional	2021/12/26	2022/12/25
DLF104	AC Power Source	2021/12/26	2022/12/25
DLF507	DC Power Source	2021/12/26	2022/12/25
DLF102	Power Meter	2021/12/26	2022/12/25
DLF111	Temperature & Humidity Datalogger	2021/12/26	2022/12/25
DLF119	Power Meter	2021/12/26	2022/12/25
DLF031	Temperature data logger	2021/12/26	2022/12/25
DLF022	Digital power meter	2021/12/26	2022/12/25
DLF003	Temperature & Humidity Datalogger	2021/12/26	2022/12/25

***** End of Test Report*****