

# Original Data

## Relevant Standards

- IES LM-79-2008
- ANSI C82.77:2014

## Prepared For RAB lighting INC

408 W 14th St New York, NY 10014, USA (888) 722-1000

## Prepared By RAB lighting INC

408 W 14th St New York, NY 10014, USA (888) 722-1000

**Project Number**

**Data Number**

**Test Date**  
**2022/9/28**

## 1.0 Test List

Test Item	Test	Test Date	Model Number	Sample No.
1	Integrating Sphere Test	2022/9/28	PLC-9.5-O-840-HYB-G24C	A1
2	Goniophotometer Test	2022/9/28	PLC-9.5-O-840-HYB-G24C	A1
3	THD and PF Test	2022/9/28	PLC-9.5-O-840-HYB-G24C	A1

## 1.1 Test Summary

Requirement Category	Test Method	Requirements	Test value
<b>Integrating Sphere system</b>			
Power (W)	IES LM-79-2008	9.5 ±10%	9.047
Lamp Output for bare lamp (lm)	IES LM-79-2008	1250 ±10%	1286
Lamp Efficacy (lm/W)	IES LM-79-2008	> 118.4	137.9
Allowable CCTs* (K)	IES LM-79-2008	7 step	5029±283
		4 step	5029±220
		7 step	3985±275
		4 step	3985±154
		7 step	3465±245
		4 step	3465±124
		7 step	3045±175
		4 step	3045±100
		7 step	2725 ± 145
		4 step	2725 ± 83
CRI	IES LM-79-2008 CIE 13.3-1995	>80	81.5
R9	IES LM-79-2008 CIE 13.3-1995	>0	6
Rf	ANSI/IES TM-30-18	>70	83
Rg	ANSI/IES TM-30-18	>89	96
Rcs,h1	ANSI/IES TM-30-18	Rcs=>-12%,h1<=23%	
Power Factor	ANSI C82.77:2014	>0.9	0.91
Total Harmonic Distortion (A%)	ANSI C82.77:2014	<25%	16.44%
<b>Goniophotometer system</b>			
Lamp Output (lm)	IES LM-79-2008	1250 ±10%	1307.0
Luminaire Efficacy(lm/W)	IES LM-79-2008	> 118.4	146.1
Beam Angle	IES LM-79-2008		344.2

## 2.0 Production Description

**Luminaire Description:** PLC-9.5-O-840-HYB-G24Q

**Electrical Specification:** 120V~277V,50/60HZ

**Light source:**

**Manufacturer Of Light Source:** Seoul Semiconductor Co.,LTD

### Photos of Luminaire Characteristics



### 3.0 LM-79 Measurement and Test Results

#### 3.1 Integrating Sphere Test

Model No.	PLC-9.5-O-840-HYB-G24Q	Sample ID.	A1
Opreate time (Min.)	15	Stabilization time (Min.)	15
Temperature (°C)	25.3	Humidity %	55

Test Method
<p>The samples were tested according to the IES LM-79-2008.</p> <p>Photometric paramters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at 25° C ± 1° C.</p> <p>The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere.</p> <p>The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ±0.2 percent under load.</p> <p>The sample was measured using 4π geometry and operated at rated voltage and was stabilized before measurement. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral radiant flux measurements taken at 1 nm intervals over the range of 380 to 780 nm.</p>

#### Test Conditions

Temperature (°C)	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Flux (lm)	Efficacy (lm/W)
25.3	120.00	60.00	0.077	9.047	0.9811	1289.0	142.5
25.3	277.02	60.00	0.037	9.323	0.9077	1286.0	137.9


#### Test Result

Tc(K)	色差(Duv)	Rf	Rg	Ra	R9	SDCM
3899	2.2E-03	83	96	81.5	5.7	2.9
3901	2.1E-03	83	96	81.5	5.8	2.8

### 3.1 Integrating Sphere Test


#### Spectroradiometric Parameters

120V









R1 =79.7 R2 =86.2 R3 =92.0 R4 =82.0 R5 =79.7 R6 =81.5 R7 =86.4  
 R8 =64.5 R9 =5.7 R10=67.8 R11=81.1 R12=59.6 R13=80.9 R14=95.4 R15=73.4

277V



R1 =79.8 R2 =86.3 R3 =92.1 R4 =81.9 R5 =79.7 R6 =81.5 R7 =86.4  
 R8 =64.5 R9 =5.8 R10=67.9 R11=81.0 R12=59.6 R13=81.0 R14=95.5 R15=73.5

### 3.2 Integrating Sphere Test - Minimum CCT



### 3.3 Goniophotometer Test

Model No.	PLC-9.5-O-840-HYB-G24Q	Sample ID.	0
Operate time (Min.)	15	Stabilization time (Min.)	15

#### Test Method

The samples were tested according to the IES LM-79-2008. Photometric parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at 25° C + 1° C. The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere. The voltage of an AC power supply (RMS voltage) or DC power supply (instantaneous voltage) applied to the device under test shall be regulated to within ± 0.2 percent under load.

The samples were operated at rated voltage and was stabilized before measurement. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 0.5o vertical intervals and 10o horizontal intervals.

#### Test Conditions


Temperature (°C)	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
25.3	120.00	60.00	0.076	8.9	0.981

#### Test Result

Flux(lm)	Beam Angle	Zonal Lumen Requirement(0°-60°)	SC (0°-180°)	SC (90°-270°)	Efficacy (lm/W)
1307.0	344.2	19.0%	0.16	0.21	146.1

### 3.3 Goniophotometer Test

#### Light Distribution Curve



#### Zonal Lumen Summary

Zone	Lumens	%Lamp	%Fixt	Zone	Lumens
0-20	9.97	N.A.	0.80	0-10	1.43
0-30	33.23	N.A.	2.50	10-20	8.54
0-40	77.96	N.A.	6.00	20-30	23.26
0-60	247.69	N.A.	19.00	30-40	44.73
0-80	516.15	N.A.	39.50	40-50	70.93
0-90	670.18	N.A.	51.30	50-60	98.80
10-90	668.75	N.A.	51.20	60-70	124.49
20-40	67.99	N.A.	5.20	70-80	143.98
20-50	138.91	N.A.	10.60	80-90	154.03
40-70	294.21	N.A.	22.50	90-100	152.98
60-80	268.46	N.A.	20.60	100-110	140.90
70-80	143.98	N.A.	11.00	110-120	119.81
80-90	154.03	N.A.	11.80	120-130	93.16
90-110	293.88	N.A.	22.50	130-140	64.98
90-120	413.69	N.A.	31.70	140-150	39.23
90-130	506.85	N.A.	38.80	150-160	18.88
90-150	611.06	N.A.	46.80	160-170	5.75
90-180	636.07	N.A.	48.70	170-180	0.39
110-180	342.19	N.A.	26.20		
0-180	1306.25	N.A.	100.00		

## 5.0 THD and PF Test

Model No.	PLC-9.5-O-840-HYB-G24Q	Sample ID.	A1
Temperature (°C)	25.3	Humidity %	49

### Test Method

The samples were tested according to the ANSI C82.77:2002.

The total harmonic distortion shall be measured to the 40th order.

The ambient temperature condition was maintained at 25° C ± 1° C. The sample measurements were made using a digital power meter and power supply. The sample was operated at rated voltage and was stabilized before measurement. The total harmonic distortion were calculated.

### Test Results

Temperature (°C)	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	THD
25.3	120.00	60.00	0.077	9.0	0.981	16.44%
25.3	277.02	60.00	0.037	9.3	0.908	15.20%