



Select Series LED Wrap Light

Product Specifications



The TCP Select Series LED Wrap Light offers superior light output in a maintenance-free fixture. With a durable metal frame, and a glare free, impact resistant frosted lens, you can install these fixtures and relax. Built to industry standard measurements, installation is quick and easy, and provides for easy upgrading.

Reasons to choose the LED Select Series LED Wrap Light from TCP

- Energy efficient LED luminaire
- Smooth, uniform dimming (0-10V)
- Instant on, no warm up time for full light
- Long-life: 50,000 hours
- Replaces traditional linear fluorescent systems
- Heavy-duty steel housing

Ideal Applications

- Warehouses & Distribution Centers
- Commercial Facilities
- Aisles (Open & Stock)
- Restrooms
- Corridors
- Stairwells
- Hallways



Select Series LED Wrap Light

Applications

TCP's Select Series LED Wrap Light offers a versatile solution for both new construction and replacing old linear fluorescent systems. With its durable construction, superior lighting output, and long lifespan, it is perfect for a wide variety of commercial applications. These fixtures come standard with an easy-access wiring compartment that allows for efficient installation.

Construction

- Housing: durable steel construction
- Finish: powder coated, post-painted white
- Large wiring compartment and knock-outs to accommodate lighting controls
- Easy surface mount, suspended or pendant installation

Electrical

- Universal 120-277V
- cULus damp location rated
- 0-10V dimming driver (standard)
- 130 lumens per watt
- Easy-to-access wiring compartment
- System rated for long 50,000 hour life

Optics

- High impact, acrylic lens comes standard to protect the LEDs and minimize glare
- Delivers bright, white light and excellent uniformity




Listings

UL and cUL listed
RoHS Compliant

Warranty

Five year limited warranty against defects in manufacturing.



Catalog Ordering Matrix

Example: WR4UZDSW3CCT

FAMILY	SIZE	VOLTAGE	CONTROLS/ DIMMING	LUMEN PACKAGE (POWER) ^{1,2}	COLOR TEMPERATURE	FACTORY INSTALLED OPTIONS
WR – Wrap Light	4 – 4 Foot	U – 120V-277V	ZD – 0-10V Dimming	SW3 – 5200/4550/3900L (40/35/30W)	CCT – 35K/40K/50K Color Selectable	Blank – None

¹ Approximate lumen output. Actual performance may vary based on CCT, options selected and end user application.

² Actual wattage may differ by +/- 10%.

For the most up-to-date specs and warranty information, please visit www.tcp.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP JAN 2026/WF538352



RoHS COMPLIANT

5 YEAR WARRANTY