

**LM-79-08 Test Report**  
For  
**RAB LIGHTING INC**

**(Brand Name: N/A)**

170 Ludlow Ave, PO BOX 970, Northvale, NJ 07647-2305 USA

**Model name(s):**  
**WFRX-4D**

**Report Type:** Testing and Report According to IES LM-79-2008

**Type of  
Luminaire:** Downlights

**Report Date:** 2024-11-29


**Prepared By:**

Test & Report By:



Engineer: Sun Fangfang

Review By:



Manager: Huang Qichong

<b>1.1 Rated Values:</b>	
Rated Voltage / Frequency	120V-277Vac, 60 Hz
Nominal Power	8.0W/10.0W/12.0W
Rated Initial Lamp Lumen	675lm/825lm/1100lm (mode 5000K)
Declared CCT	2700K/3000K/3500K/4000K/5000K

### 1.2 Test Specifications:

Test item	<ol style="list-style-type: none"> <li>1. Total Luminous Flux</li> <li>2. Luminous Distribution Intensity</li> <li>3. Luminous Efficacy</li> <li>4. Correlated Color Temperature</li> <li>5. Color Rendering Index</li> <li>6. Chromaticity Coordinate</li> <li>7. Electrical Parameters</li> </ol>
Reference Standard	<ol style="list-style-type: none"> <li>1. IES LM-79-2008 Electrical and Photometric Measurements of Solid-State Lighting Products</li> <li>2. ANSI C78.377-2015 Specifications for the Chromaticity of Solid State Lighting Products</li> <li>3. CIE 13.3-1995 Method of Measuring and Specifying Colour Rendering Properties of Light Sources</li> <li>4. CIE 15-2004 Technical Report Colorimetry</li> <li>5. IESNA LM-16-93 Practical Guide to Colorimetry of Light Source</li> <li>6. IESNA TM-16-05 Technical Memorandum on Light Emitting Diode (LED) Sources and Systems</li> </ol>
Reference Work Instruction	QD25

### 1.3 Test Methods

<p><b>1) Photometric and Light Distribution Measurement – Goniophotometer Method:</b> Photometric parameters were measured using the goniophotometer and software. The ambient temperature shall be maintained at 25°C ±1°C, measured at a point not more than 1 m from the sample and at the same height as the sample. The sample was operated at 120 or rated Volts AC, 60Hz. It was stabilized before measurement was made. Luminous flux, luminaire efficacy, zonal lumen were calculated from the software taken at 1°vertical intervals and 22.5°horizontal intervals.</p>
<p><b>2) Chromaticity Measurement – Sphere-Spectroradiometer Method:</b> Chromaticity parameters were measured using an integrating sphere, a spectroradiometer and software. The ambient temperature condition inside the sphere was maintained at 25°C ±1°C. The sample measurements were made using a spectroradiometer connected by a fiber optic cable and detector through the detector port of the integrating sphere. The sample was operated at 120 or rated Volts AC, 60Hz. It was stabilized before measurement was made. Chromaticity coordinates, correlated color temperature and color rendering index were calculated from the spectral power distribution taken at 5 nm intervals over the range of 380 to 780 nm</p>
<p><b>3) Electrical Measurements:</b> Electrical parameters were measured using power meters incorporated in goniophotometer or sphere-spectroradiometer system. The ambient temperature surrounding the sample was maintained at 25°C ±1°C. The sample was operated at 120 or rated Volts AC, 60Hz. It was stabilized before measurement was made. Voltage, frequency, current, power, power factor and total harmonic distortion were measured by and read from the power meter.</p>

**2.1.1 Electrical, Photometric and Chromaticity Measurements**

<b>Test date</b>	2024-11-27	<b>Test Ambient:</b>	25.1 °C
<b>Test Orientation</b>	As intended	<b>Stabilization Time (min)</b>	90
<b>Model Number</b>	WFRX-4D	5000K	

**Electrical Measurement:**

Sample No.	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
202411200017	120.0	60	0.084	10.00	0.995

**Chromaticity Measurement - Sphere-Spectroradiometer Method:**


Parameter	Result	Special Color Rendering Indices			
Test Voltage (V)	120	R1	96	R9	74
Frequency (Hz)	60	R2	96	R10	89
CCT (K)	5091	R3	94	R11	95
Duv	0.0035	R4	96	R12	74
Chromaticity (x, y)	x=0.3431 y=0.3571	R5	95	R13	96
Chromaticity (u', v')	u'=0.2080 v'=0.4870	R6	94	R14	96
Color Rendering Index (CRI)	94.8	R7	96	R15	94
R9	74	R8	91	--	--
Rg	100				
Rf	93				
Rcs,h1%	-4				







**Photometric Measurement – Goniophotometer Method:**

Parameter	Result
Test Voltage (V)	120.0
Frequency (Hz)	60
Total Luminous (lm)	1103.1
Luminous Efficacy (lm/W)	110.31
Beam Angle (°)	109.0
Center Beam Candle Power (cd)	401.6

Parameter	Result
Test Voltage (V)	277.0
Frequency (Hz)	60
Total Luminous (lm)	1153.0
Luminous Efficacy (lm/W)	104.06

# Spectral Power Distribution & Chromaticity Diagram









# Zonal Lumen Tabulation

Zonal Lumen Summary		
Zone	Lumens	% Luminaire
0-30	307.4	27.9%
0-40	500.8	45.4%
0-60	876.6	79.5%
60-90	226.6	20.5%
70-100	94.0	8.5%
90-120	0.0	0.0%
0-90	1103.1	100.0%
90-180	0.0	0.0%
0-180	1103.1	100.0%

Lumens Per Zone					
Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	37.9	3.4%	90-100	0.0	0.0%
10-20	107.9	9.8%	100-110	0.0	0.0%
20-30	161.6	14.6%	110-120	0.0	0.0%
30-40	193.4	17.5%	120-130	0.0	0.0%
40-50	198.9	18.0%	130-140	0.0	0.0%
50-60	176.9	16.0%	140-150	0.0	0.0%
60-70	132.6	12.0%	150-160	0.0	0.0%
70-80	74.9	6.8%	160-170	0.0	0.0%
80-90	19.1	1.7%	170-180	0.0	0.0%

## Photometric Data





## 2.1.2 Electrical, Photometric and Chromaticity Measurements

Test date	2024-11-27	Test Ambient:	25.1 °C
Test Orientation	As intended	Stabilization Time (min)	90
Model Number	WFRX-4D	2700K	

### Electrical Measurement:

Sample No.	Voltage (Vac)	Frequency (Hz)	Current (A)	Power (W)	Power Factor
202411200017	120.0	60	0.084	10.00	0.995

### Chromaticity Measurement - Sphere-Spectroradiometer Method:


Parameter	Result	Special Color Rendering Indices			
Test Voltage (V)	120	R1	95	R9	58
Frequency (Hz)	60	R2	96	R10	89
CCT (K)	2776	R3	96	R11	99
Duv	0.0036	R4	97	R12	83
Chromaticity (x, y)	x=0.4598 y=0.4204	R5	94	R13	95
Chromaticity (u', v')	u'=0.2582 v'=0.5310	R6	98	R14	97
Color Rendering Index (CRI)	94.0	R7	93	R15	89
R9	58	R8	83	--	--
Rg	97				
Rf	93				
Rcs,h1%	-6				







### Photometric Measurement – Goniophotometer Method:

Parameter	Result
Test Voltage (V)	120.0
Frequency (Hz)	60
Total Luminous (lm)	1063.7
Luminous Efficacy (lm/W)	106.37

Parameter	Result
Test Voltage (V)	277.0
Frequency (Hz)	60
Total Luminous (lm)	1110.0
Luminous Efficacy (lm/W)	100.27

# Spectral Power Distribution & Chromaticity Diagram





**2.1.3 Electrical, Photometric and Chromaticity Measurements**

<b>Test date</b>	2024-11-27	<b>Test Ambient:</b>	25.1 °C
<b>Test Orientation</b>	As intended	<b>Stabilization Time (min)</b>	90
<b>Model Number</b>	WFRX-4D	3000K	

**Electrical Measurement:**

Sample No.	Voltage (Vac)	Frequency (Hz )	Current (A)	Power (W)	Power Factor
202411200017	120.0	60	0.083	10.00	0.995

**Chromaticity Measurement - Sphere-Spectroradiometer Method:**


Parameter	Result	Special Color Rendering Indices			
Test Voltage (V)	120	R1	97	R9	65
Frequency (Hz)	60	R2	97	R10	92
CCT (K)	3008	R3	97	R11	97
Duv	0.0017	R4	98	R12	83
Chromaticity (x, y)	x=0.4388 y=0.4090	R5	96	R13	97
Chromaticity (u', v')	u'=0.2497 v'=0.5236	R6	97	R14	97
Color Rendering Index (CRI)	95.2	R7	94	R15	92
R9	65	R8	86	--	--
Rg	99				
Rf	93				
Rcs,h1%	-5				







**Photometric Measurement – Goniophotometer Method:**

Parameter	Result
Test Voltage (V)	120.0
Frequency (Hz)	60
Total Luminous (lm)	1078.6
Luminous Efficacy (lm/W)	107.86

Parameter	Result
Test Voltage (V)	277.0
Frequency (Hz)	60
Total Luminous (lm)	1129.0
Luminous Efficacy (lm/W)	101.98

# Spectral Power Distribution & Chromaticity Diagram





**2.1.4 Electrical, Photometric and Chromaticity Measurements**

<b>Test date</b>	2024-11-27	<b>Test Ambient:</b>	25.1 °C
<b>Test Orientation</b>	As intended	<b>Stabilization Time (min)</b>	90
<b>Model Number</b>	WFRX-4D	3500K	

**Electrical Measurement:**

Sample No.	Voltage (Vac)	Frequency (Hz )	Current (A)	Power (W)	Power Factor
202411200017	120.0	60	0.082	9.89	0.995

**Chromaticity Measurement - Sphere-Spectroradiometer Method:**


Parameter	Result	Special Color Rendering Indices			
Test Voltage (V)	120	R1	98	R9	75
Frequency (Hz)	60	R2	98	R10	94
CCT (K)	3522	R3	96	R11	96
Duv	0.0002	R4	98	R12	79
Chromaticity (x, y)	x=0.4043 y=0.3906	R5	98	R13	99
Chromaticity (u', v')	u'=0.2351 v'=0.5111	R6	96	R14	97
Color Rendering Index (CRI)	96.4	R7	96	R15	95
R9	75	R8	91	--	--
Rg	101				
Rf	93				
Rcs,h1%	-3				

**Photometric Measurement – Goniophotometer Method:**







Parameter	Result
Test Voltage (V)	120.0
Frequency (Hz)	60
Total Luminous (lm)	1102.5
Luminous Efficacy (lm/W)	111.48

Parameter	Result
Test Voltage (V)	277.0
Frequency (Hz)	60
Total Luminous (lm)	1162.0
Luminous Efficacy (lm/W)	106.08

# Spectral Power Distribution & Chromaticity Diagram



# TM30



**2.1.5 Electrical, Photometric and Chromaticity Measurements**

<b>Test date</b>	2024-11-27	<b>Test Ambient:</b>	25.1 °C
<b>Test Orientation</b>	As intended	<b>Stabilization Time (min)</b>	90
<b>Model Number</b>	WFRX-4D	4000K	

**Electrical Measurement:**

Sample No.	Voltage (Vac)	Frequency (Hz )	Current (A)	Power (W)	Power Factor
202411200017	120.0	60	0.083	9.93	0.995

**Chromaticity Measurement - Sphere-Spectroradiometer Method:**


Parameter	Result	Special Color Rendering Indices			
Test Voltage (V)	120	R1	98	R9	79
Frequency (Hz)	60	R2	98	R10	93
CCT (K)	4114	R3	95	R11	96
Duv	0.0005	R4	98	R12	75
Chromaticity (x, y)	x=0.3759 y=0.3750	R5	97	R13	99
Chromaticity (u', v')	u'=0.2228 v'=0.5002	R6	96	R14	97
Color Rendering Index (CRI)	96.5	R7	97	R15	96
R9	79	R8	93	--	--
Rg	101				
Rf	93				
Rcs,h1%	-3				

**Photometric Measurement – Goniophotometer Method:**







Parameter	Result
Test Voltage (V)	120.0
Frequency (Hz)	60
Total Luminous (lm)	1110.3
Luminous Efficacy (lm/W)	111.81

Parameter	Result
Test Voltage (V)	277.0
Frequency (Hz)	60
Total Luminous (lm)	1162.0
Luminous Efficacy (lm/W)	105.68

# Spectral Power Distribution & Chromaticity Diagram





# TM30



Sample No.	Wattage and CCT setting	Test Voltage(V)	Flux(lm)	P(W)	Luminous Efficacy lm/W
WFRX-4D	8W-5000K setting	120	727.5	6.86	106.05
		277	790.0	7.95	99.43
	10W-5000K setting	120	905.1	8.66	104.52
		277	952.0	9.83	96.82
	12W-2700K setting	120	1063.7	10.00	106.37
		277	1110.0	11.07	100.27
	12W-3000K setting	120	1078.6	10.00	107.86
		277	1129.0	11.07	101.98
	12W-3500K setting	120	1102.5	9.89	111.48
		277	1162.0	10.95	106.08
	12W-4000K setting	120	1110.3	9.93	111.81
		277	1162.0	11.00	105.68
	12W-5000K setting	120	1103.1	10.00	110.31
		277	1153.0	11.08	104.06

**3. Product Photo**



**\*\*\*\*\* END OF REPORT \*\*\*\*\***